

Linear Power Supply/Charger Boards		
MODEL	DESCRIPTION	PRICE
AL624	Linear Power Supply/Charger - 6VDC or 12VDC @ 1.2 amp or 24VDC @ 750mA.	18.49
DPS1	DIN Rail Mount Linear Power Supply/Charger - 6VDC or 12VDC @ 1.2 amp or 24VDC @ 750mA, Includes snap track & mounting clips (order DIN Rail separately).	32.93
AL62412C	Linear Power Supply/Charger - 12VDC @ 1.2 amp, 12VDC/4AH battery & 16.5VAC/20VA plug-in xfmr.	74.89
AL62412CX	Linear Power Supply/Charger - 12VDC @ 1.2 amp, 12VDC/7AH battery & 16.5VAC/20VA plug-in xfmr.	81.78
AL62424C	Linear Power Supply/Charger - 24VDC @ 750mA, two 12VDC/4AH batteries & 24VAC/40VA plug-in xfmr.	117.33
PM212	Linear Power Supply/Charger - 12VDC @ 1 amp, AC & battery monitoring.	40.00
PM224	Linear Power Supply/Charger - 24VDC @ 750mA, AC & battery monitoring.	40.00
LPS3	Linear Power Supply/Charger - 12VDC or 24VDC @ 2.5 amp, 5 amp on demand.	65.33
LPS3AC	Linear Power Supply/Charger - 12VDC or 24VDC @ 2.5 amp, 5 amp on demand, AC monitoring.	88.89
Linear Power Supply/Chargers with Enclosures		
MODEL	DESCRIPTION	PRICE
AL624E	Linear Power Supply/Charger - 6VDC or 12VDC @ 1.2 amp or 24VDC @ 750mA, encl. 8.5"H x 7.5"W x 3.5"D.	56.67
AL624ET	Linear Power Supply/Charger - 6VDC or 12VDC @ 1.2 amp or 24VDC @ 750mA, 16VAC/20VA plug-in xfmr, encl. 8.5"H x 7.5"W x 3.5"D.	68.33
LPS3C12X	Linear Power Supply/Charger - 12VDC @ 2.5 amp, 5 amp on demand, encl. 13.5"H x 13"W x 3.25"D. 115VAC input.	210.00
LPS3C24X	Linear Power Supply/Charger - 24VDC @ 2.5 amp, 5 amp on demand, encl. 13.5"H x 13"W x 3.25"D. 115VAC input.	210.00
LPS3WP12	Linear Power Supply/Charger - 12VDC @ 2.5 amp, 5 amp on demand, NEMA4/IP65 rated outdoor encl. 12"H x 8"W x 6"D, 115VAC input.	298.89
LPS3WP24	Linear Power Supply/Charger - 24VDC @ 2.5 amp, 5 amp on demand, NEMA4/IP65 rated outdoor encl. 12"H x 8"W x 6"D, 115VAC input.	298.89
LPS5C12X	Linear Power Supply/Charger - 12VDC @ 3.5 amp, 8 amp on demand, AC & battery monitoring, encl. 13.5"H x 13"W x 3.25"D, 115VAC input.	242.22
LPS5C24X	Linear Power Supply/Charger - 24VDC @ 3.5 amp, 8 amp on demand, AC & battery monitoring, encl. 13.5"H x 13"W x 3.25"D, 115VAC input.	242.22
Switch Mode Power Supply/Charger Boards		
MODEL	DESCRIPTION	PRICE
SMP3	Power Supply/Charger - 6VDC, 12VDC or 24VDC @ 2.5 amp.	48.13
DPS3	DIN Rail Mount Power Supply/Charger - 6VDC, 12VDC or 24VDC rated @ 2.5 amp, Includes snap track & mounting clips (order DIN Rail separately).	62.56
SMP312C	Power Supply/Charger - 12VDC @ 2.5 amp power supply, 12VDC/4AH battery & 16.5VAC/40VA plug-in xfmr.	110.89
SMP312CX	Power Supply/Charger - 12VDC @ 2.5 amp power supply, 12VDC/7AH battery & 16.5VAC/40VA plug-in xfmr.	116.11
SMP3PM	Power Supply/Charger - 12VDC or 24VDC @ 2.5 amp, AC & battery monitoring.	74.67
SMP5	Power Supply/Charger - 6VDC, 12VDC or 24VDC @ 4 amp.	71.00
DPS5	DIN Rail Mount Power Supply/Charger - 6VDC, 12VDC or 24VDC rated @ 4 amp, Includes snap track & mounting clips (order DIN Rail separately).	85.44
SMP5PM	Power Supply/Charger - 12VDC or 24VDC @ 4 amp, AC & battery monitoring.	105.00
SMP7	Power Supply/Charger - 12VDC or 24VDC @ 6 amp.	135.33
SMP7PM	Power Supply/Charger - 12VDC or 24VDC @ 6 amp, AC & battery monitoring.	161.11
SMP10	Power Supply/Charger - 12VDC or 24VDC @ 10 amp.	198.33
SMP10PM	Power Supply/Charger - 12VDC or 24VDC @ 10 amp, AC & battery monitoring.	231.67
Switch Mode Power Supply/Chargers with Enclosures		
MODEL	DESCRIPTION	PRICE
SMP3E	Power Supply/Charger - 6VDC, 12VDC or 24VDC @ 2.5 amp, encl. 8.5"H x 7.5"W x 3.5"D.	81.47
SMP3CTX	Power Supply/Charger - 12VDC or 24VDC @ 2.5 amp, encl. 13.5"H x 13"W x 3.25"D, 115/230VAC input.	192.67

Switch Mode Power Supply/Chargers with Enclosures		
MODEL	DESCRIPTION	PRICE
SMP3PMCTX	Power Supply/Charger - 12VDC or 24VDC @ 2.5 amp, AC & battery monitoring, encl. 13.5"H x 13"W x 3.25"D, 115/230VAC input.	219.33
SMP5CTX	Power Supply/Charger - 12VDC or 24VDC @ 4 amp, encl. 13.5"H x 13"W x 3.25"D, 115/230VAC input.	225.33
SMP5PMCTX	Power Supply/Charger - 12VDC or 24VDC @ 4 amp, AC & battery monitoring, encl. 13.5"H x 13"W x 3.25"D, 115/230VAC input.	252.00
SMP7CTX	Power Supply/Charger - 12VDC or 24VDC @ 6 amp, encl. 13.5"H x 13"W x 3.25"D, 115VAC input.	295.56
SMP7PMCTX	Power Supply/Charger - 12VDC or 24VDC @ 6 amp, AC & battery monitoring, encl. 13.5"H x 13"W x 3.25"D, 115VAC input.	322.22
SMP10C12X	Power Supply/Charger - 12VDC @ 10 amp, encl. 13.5"H x 13"W x 3.25"D, 115VAC input.	352.22
SMP10C24X	Power Supply/Charger - 24VDC @ 10 amp, encl. 15.5"H x 12"W x 4.5"D, 115VAC input.	500.00
SMP10PMC12X	Power Supply/Charger - 12VDC @ 10 amp, AC & battery monitoring, encl. 13.5"H x 13"W x 3.25"D, 115VAC input.	385.56
SMP10PMC24X	Power Supply/Charger - 24VDC @ 10 amp, AC & battery monitoring, encl. 15.5"H x 12"W x 4.5"D, 115VAC input.	533.33
Off-line Switching Power Supply/Charger Boards		
MODEL	DESCRIPTION	PRICE
OLS20	Power Supply/Charger - 12VDC @ 1 amp or 24VDC @ 500 mA, 115VAC input	47.22
OLS75	Power Supply/Charger - 12VDC or 24VDC @ 2.5 amp, AC & battery monitoring, 115/230VAC input.	144.44
OLS120	Power Supply/Charger - 12VDC or 24VDC @ 4 amp, AC & battery monitoring, 115/230VAC input.	177.78
OLS180	Power Supply/Charger - 12VDC or 24VDC @ 6 amp, AC & battery monitoring, 115VAC input.	255.56
OLS200	Power Supply/Charger - 12VDC @ 10 amp, AC & battery monitoring, 115VAC input.	255.56
OLS250	Power Supply/Charger - 24VDC @ 10 amp, AC & battery monitoring, 115VAC input.	400.00
UL Recognized Power Supply/Charger Boards		
MODEL	DESCRIPTION	PRICE
AL125ULB	Power Supply/Charger - 12VDC or 24VDC @ 1 amp, latching/non-latching fire alarm disconnect, (24VAC 40VA Plug-in xfmr required), UL Recognized.	62.22
AL175ULB	Power Supply/Charger - 12VDC or 24VDC @ 1.75 amp, latching/non-latching fire alarm disconnect, (28VAC 56VA xfmr required), UL Recognized.	93.33
AL176ULB	Power Supply/Charger - 12VDC or 24VDC @ 1.75 amp, AC fail & low battery monitoring, (28VAC 56VA xfmr required), UL Recognized.	93.33
AL201ULB	Power Supply/Charger - 12VDC or 24VDC @ 1.75 amp, AC & battery monitoring, UL Recognized.	93.33
AL300ULXB	Power Supply/Charger - 12VDC or 24VDC @ 2.5 amp, AC & battery monitoring, Class 2 power limited output, 115VAC input, UL Recognized.	176.67
AL400ULB	Power Supply/Charger - 12VDC @ 4 amp or 24VDC @ 3 amp, AC & battery monitoring, Class 2 power limited output, (28VAC 175VA xfmr required), UL Recognized.	158.67
AL400ULXB	Power Supply/Charger - 12VDC @ 4 amp or 24VDC @ 3 amp, AC & battery monitoring, Class 2 power limited output, 115VAC input, UL Recognized.	209.44
AL600ULB	Power Supply/Charger - 12VDC or 24VDC @ 6 amp, AC & battery monitoring, non-power limited output, (Two 28VAC 100VA xfmr required), UL Recognized.	188.89
AL600ULXB	Power Supply/Charger - 12VDC or 24VDC @ 6 amp, AC & battery monitoring, non-power limited output, 115VAC input, UL Recognized.	333.33
AL1012ULXB	Power Supply/Charger - 12VDC @ 10 amp, AC & battery monitoring, non-power limited output, 115VAC input. UL Recognized.	377.78
AL1024ULXB	Power Supply/Charger - 24VDC @ 10 Amp, AC & battery monitoring, non-power limited output, 115VAC input. UL Recognized.	422.22

UL Listed Power Supply/Chargers with Enclosures		
MODEL	DESCRIPTION	PRICE
AL100UL	Power Supply/Charger - 12VDC @ 750mA, Class 2 power limited output, encl. 8.5"H x 7.5" W x 3.5"D, 16VAC 20VA Plug-in xfmr required, UL Listed (UL603).	102.67
AL176UL	Power Supply/Charger - 12VDC or 24 VDC @ 1.75 amp, AC & battery monitoring, Class 2 power limited output, encl. 8.5"H x 7.5"W x 3.5"D, 115VAC input, cULus Listed (UL294).	166.67
AL176ULX	Power Supply/Charger - 12VDC or 24 VDC @ 1.75 amp, AC & battery monitoring, Class 2 power limited output, encl. 13.5"H x 13"W x 3.25"D., 115VAC input, cULus Listed (UL294).	188.89
AL201UL	Power Supply/Charger - 12VDC @ 1.75 amp, AC & battery monitoring, Class 2 power limited output, encl. 8.5"H x 7.5" W x 3.5"D, 115VAC input, UL Listed (UL294/UL603).	133.00
AL300ULX	Power Supply/Charger - 12VDC or 24VDC @ 2.5 amp, AC & battery monitoring, Class 2 power limited output, encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL294/UL603/UL1069/UL1481), cUL Listed, CSFM & MEA Approved.	242.78
AL300ULXR	Power Supply/Charger - 12VDC or 24VDC @ 2.5 amp, AC & battery monitoring, Class 2 power limited output, red encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL294/UL603/UL1069/UL1481), cUL Listed, CSFM & MEA Approved.	242.78
AL300ULXD	Power Supply/Charger - 12VDC or 24VDC @ 2.5 amp, AC & battery monitoring, Class 2 power limited output, encl. 15.5"H x 12"W x 4.5"D, 115/230VAC input, UL Listed (UL294/UL603/UL1069/UL1481), CSFM & MEA Approved.	265.56
AL400UL	Power Supply/Charger - 12VDC @ 4 amp or 24VDC @ 3 amp, AC & battery monitoring, Class 2 power limited output, encl. 12.25"H x 7.5"W x 4.5"D, 115VAC input, UL Listed (UL294/UL603/UL1069/UL1481), cUL Listed, CSFM & MEA Approved.	268.33
AL400ULX	Power Supply/Charger - 12VDC @ 4 amp or 24VDC @ 3 amp, AC & battery monitoring, Class 2 power limited output, encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL294/UL603/UL1069/UL1481), cUL Listed, CSFM, MEA & FM Approved.	303.33
AL400ULXR	Power Supply/Charger - 12VDC @ 4 amp or 24VDC @ 3 amp, AC & battery monitoring, Class 2 power limited output, red encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL294/UL603/UL1069/UL1481), cUL Listed, CSFM, MEA & FM Approved.	303.33
AL600ULX	Power Supply/Charger - 12VDC or 24VDC @ 6 amp, AC & battery monitoring, non-power limited output, encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL294/UL1481), cUL Listed, CSFM, MEA & FM Approved.	433.33
AL600ULXR	Power Supply/Charger - 12VDC or 24VDC @ 6 amp, AC & battery monitoring, non-power limited output, red encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL294/UL1481), cUL Listed, CSFM, MEA & FM Approved.	433.33
AL600ULXD	Power Supply/Charger - 12VDC or 24VDC @ 6 amp, AC & battery monitoring, non-power limited output, encl. 15.5"H x 12"W x 4.5"D, 115/230VAC input, UL Listed (UL294/UL1481).	455.56
AL1012ULX	Power Supply/Charger - 12VDC @ 10 amp, AC & battery monitoring, non-power limited output, encl. 15.5"H x 12"W x 4.5"D, 115VAC input, UL Listed (UL294), cUL Listed.	466.67
AL1024ULX	Power Supply/Charger - 24VDC @ 10 amp, AC & battery monitoring, non-power limited output, encl. 15.5"H x 12"W x 4.5"D, 115VAC input, UL Listed (UL294/UL1481), cUL Listed, CSFM, MEA & FM Approved.	555.56
AL1024ULXR	Power Supply/Charger - 24VDC @ 10 amp, AC & battery monitoring, non-power limited output, red encl. 15.5"H x 12"W x 4.5"D, 115VAC input, UL Listed (UL294/UL1481), cUL Listed, CSFM, MEA & FM Approved.	555.56
eFlow Power Supply/Chargers with Enclosures		
MODEL	DESCRIPTION	PRICE
EFLOW3N	Two (2) Output Power Supply/Charger w/Fire Alarm Disconnect - 12VDC or 24VDC @ 2 amp max, One (1) aux. output (unswitched) plus one (1) aux. output (switched), Class 2 power limited, AC & battery monitoring, Low power shutdown, Over voltage protection (OVP), encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL294/UL603/UL1481), cUL Listed (ULC-S318-96)	276.11

Multi-Output Power Supply/Chargers with Enclosures (Fused)		
MODEL	DESCRIPTION	PRICE
AL300ULPD4	4 Output Power Supply/Charger - 12VDC or 24VDC @ 2.5 amp, fused Class 2 power limited outputs, AC & battery monitoring, encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL294/UL603/UL1069/UL1481), cUL Listed.	296.11
AL300ULPD8	8 Output Power Supply/Charger - 12VDC or 24VDC @ 2.5 amp, fused Class 2 power limited outputs, AC & battery monitoring, encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL294/UL603/UL1069/UL1481), cUL Listed.	305.00
AL300ULXP16	16 Output Power Supply/Charger - 12VDC or 24VDC @ 2.5 amp, fused Class 2 power limited outputs, AC & battery monitoring, encl. 15.5"H x 12"W x 4.5"D, 115VAC input, UL Listed (UL294/UL603/UL1069/UL1481), cUL Listed.	367.22
AL400ULPD4	4 Output Power Supply/Charger - 12VDC @ 4 amp or 24VDC @ 3 amp, fused Class 2 power limited outputs, AC & battery monitoring, encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL294/UL603/UL1069/UL1481), cUL Listed.	336.67
AL400ULPD8	8 Output Power Supply/Charger - 12VDC @ 4 amp or 24VDC @ 3 amp, fused Class 2 power limited outputs, AC & battery monitoring, encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL294/UL603/UL1069/UL1481), cUL Listed.	345.56
AL400ULXP16	16 Output Power Supply/Charger - 12VDC @ 4 amp or 24VDC @ 3 amp, fused Class 2 power limited outputs, AC & battery monitoring, encl. 15.5"H x 12"W x 4.5"D, 115VAC input, UL Listed (UL294/UL603/UL1069/UL1481), cUL Listed.	427.78
AL600ULPD4	4 Output Power Supply/Charger - 12VDC or 24VDC @ 6 amp, fused non-power limited outputs, AC & battery monitoring, encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL294/UL1481), cUL Listed.	486.67
AL600ULPD8	8 Output Power Supply/Charger - 12VDC or 24VDC @ 6 amp, fused non-power limited outputs, AC & battery monitoring, encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL294/UL1481), cUL Listed.	495.56
AL600ULXP16	16 Output Power Supply/Charger - 12VDC or 24VDC @ 6 amp, fused non-power limited outputs, AC & battery monitoring, encl. 15.5"H x 12"W x 4.5"D, 115VAC input, UL Listed (UL294/UL1481), cUL Listed.	557.78
AL1012ULXP4	4 Output Power Supply/Charger - 12VDC @ 10 amp, fused non-power limited outputs, AC & battery monitoring, encl. 15.5"H x 12"W x 4.5"D, 115VAC input, UL Listed (UL294), cUL Listed.	521.11
AL1012ULXP8	8 Output Power Supply/Charger - 12VDC @ 10 amp, fused non-power limited outputs, AC & battery monitoring, encl. 15.5"H x 12"W x 4.5"D, 115VAC input, UL Listed (UL294), cUL Listed.	528.89
AL1012ULXP16	16 Output Power Supply/Charger - 12VDC @ 10 amp, fused non-power limited outputs, AC & battery monitoring, encl. 15.5"H x 12"W x 4.5"D, 115VAC input, UL Listed (UL294), cUL Listed.	588.89
AL1024ULXP4	4 Output Power Supply/Charger - 24VDC @ 10 amp, fused non-power limited outputs, AC & battery monitoring, encl. 15.5"H x 12"W x 4.5"D, 115VAC input, UL Listed (UL294/UL1481), cUL Listed.	608.89
AL1024ULXP8	8 Output Power Supply/Charger - 24VDC @ 10 amp, fused non-power limited outputs, AC & battery monitoring, encl. 15.5"H x 12"W x 4.5"D, 115VAC input, UL Listed (UL294/UL1481), cUL Listed.	620.00
AL1024ULXP16	16 Output Power Supply/Charger - 24VDC @ 10 amp, fused non-power limited outputs, AC & battery monitoring, encl. 15.5"H x 12"W x 4.5"D, 115VAC input, UL Listed (UL294/UL1481), cUL Listed.	684.44
SMP10PM12P4	4 Output Power Supply/Charger - 12VDC @ 10 amp, fused outputs, AC & battery monitoring, encl. 13.5"H x 13"W x 3.25"D, 115VAC input.	414.44
SMP10PM12P8	8 Output Power Supply/Charger - 12VDC @ 10 amp, fused outputs, AC & battery monitoring, encl. 13.5"H x 13"W x 3.25"D, 115VAC input.	423.33
SMP10PM12P16	16 Output Power Supply/Charger - 12VDC @ 10 amp, fused outputs, AC & battery monitoring, encl. 13.5"H x 13"W x 3.25"D, 115VAC input.	467.78
SMP10PM24P4	4 Output Power Supply/Charger - 24VDC @ 10 amp, fused outputs, AC & battery monitoring, encl. 15.5"H x 12"W x 4.5"D, 115VAC input.	614.44
SMP10PM24P8	8 Output Power Supply/Charger - 24VDC @ 10 amp, fused outputs, AC & battery monitoring, encl. 15.5"H x 12"W x 4.5"D, 115VAC input.	584.44
SMP10PM24P16	16 Output Power Supply/Charger - 24VDC @ 10 amp, fused outputs, AC & battery monitoring, encl. 15.5"H x 12"W x 4.5"D, 115VAC input.	651.78

Multi-Output Power Supply/Chargers with Enclosures (PTCs)		
MODEL	DESCRIPTION	PRICE
AL300ULPD4CB	4 Output Power Supply/Charger - 12VDC or 24VDC @ 2.5 amp, PTC Class 2 power limited outputs, AC & battery monitoring, encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL294/UL603/UL1069/UL1481), cUL Listed.	296.11
AL300ULPD8CB	8 Output Power Supply/Charger - 12VDC or 24VDC @ 2.5 amp, PTC Class 2 power limited outputs, AC & battery monitoring, encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL294/UL603/UL1069/UL1481), cUL Listed.	305.00
AL300ULXPD16CB	16 Output Power Supply/Charger - 12VDC or 24VDC @ 2.5 amp, PTC Class 2 power limited outputs, AC & battery monitoring, encl. 15.5"H x 12"W x 4.5"D, 115VAC input, UL Listed (UL294/UL603/UL1069/UL1481), cUL Listed.	367.22
AL400ULPD4CB	4 Output Power Supply/Charger - 12VDC @ 4 amp or 24VDC @ 3 amp, PTC Class 2 power limited outputs, AC & battery monitoring, encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL294/UL603/UL1069/UL1481), cUL Listed.	336.67
AL400ULPD8CB	8 Output Power Supply/Charger - 12VDC @ 4 amp or 24VDC @ 3 amp, PTC Class 2 power limited outputs, AC & battery monitoring, encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL294/UL603/UL1069/UL1481), cUL Listed.	345.56
AL400ULXPD16CB	16 Output Power Supply/Charger - 12VDC @ 4 amp or 24VDC @ 3 amp, PTC Class 2 power limited outputs, AC & battery monitoring, encl. 15.5"H x 12"W x 4.5"D, 115VAC input, UL Listed (UL294/UL603/UL1069/UL1481), cUL Listed.	427.78
AL600ULPD4CB	4 Output Power Supply/Charger - 12VDC or 24VDC @ 6 amp, PTC Class 2 power limited outputs, AC & battery monitoring, encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL294/UL1481), cUL Listed.	486.67
AL600ULPD8CB	8 Output Power Supply/Charger - 12VDC or 24VDC @ 6 amp, PTC Class 2 power limited outputs, AC & battery monitoring, encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL294/UL1481), cUL Listed.	495.56
AL600ULXPD16CB	16 Output Power Supply/Charger - 12VDC or 24VDC @ 6 amp, PTC Class 2 power limited outputs, AC & battery monitoring, encl. 15.5"H x 12"W x 4.5"D, 115VAC input, UL Listed (UL294/UL1481), cUL Listed.	557.78
AL1012ULXPD4CB	4 Output Power Supply/Charger - 12VDC @ 10 amp, PTC Class 2 power limited outputs, AC & battery monitoring, encl. 15.5"H x 12"W x 4.5"D, 115VAC input, UL Listed (UL294), cUL Listed.	521.11
AL1012ULXPD8CB	8 Output Power Supply/Charger - 12VDC @ 10 amp, PTC Class 2 power limited outputs, AC & battery monitoring, encl. 15.5"H x 12"W x 4.5"D, 115VAC input, UL Listed (UL294), cUL Listed.	528.89
AL1012ULXPD16CB	16 Output Power Supply/Charger - 12VDC @ 10 amp, PTC Class 2 power limited outputs, AC & battery monitoring, encl. 15.5"H x 12"W x 4.5"D, 115VAC input, UL Listed (UL294), cUL Listed.	588.89
AL1024ULXPD4CB	4 Output Power Supply/Charger - 24VDC @ 10 amp, PTC Class 2 power limited outputs, AC & battery monitoring, encl. 15.5"H x 12"W x 4.5"D, 115VAC input, UL Listed (UL294/UL1481), cUL Listed.	608.89
AL1024ULXPD8CB	8 Output Power Supply/Charger - 24VDC @ 10 amp, PTC Class 2 power limited outputs, AC & battery monitoring, encl. 15.5"H x 12"W x 4.5"D, 115VAC input, UL Listed (UL294/UL1481), cUL Listed.	620.00
AL1024ULXPD16CB	16 Output Power Supply/Charger - 24VDC @ 10 amp, PTC Class 2 power limited outputs, AC & battery monitoring, encl. 15.5"H x 12"W x 4.5"D, 115VAC input, UL Listed (UL294/UL1481), cUL Listed.	684.44
SMP10PM12P4CB	4 Output Power Supply/Charger - 12VDC @ 10 amp, PTC outputs, AC & battery monitoring, encl. 13.5"H x 13"W x 3.25"D, 115VAC input.	414.44
SMP10PM12P8CB	8 Output Power Supply/Charger - 12VDC @ 10 amp, PTC outputs, AC & battery monitoring, encl. 13.5"H x 13"W x 3.25"D, 115VAC input.	423.33
SMP10PM12P16CB	16 Output Power Supply/Charger - 12VDC @ 10 amp, PTC outputs, AC & battery monitoring, encl. 13.5"H x 13"W x 3.25"D, 115VAC input.	467.78
SMP10PM24P4CB	4 Output Power Supply/Charger - 24VDC @ 10 amp, PTC outputs, AC & battery monitoring, encl. 15.5"H x 12"W x 4.5"D, 115VAC input.	614.44
SMP10PM24P8CB	8 Output Power Supply/Charger - 24VDC @ 10 amp, PTC outputs, AC & battery monitoring, encl. 15.5"H x 12"W x 4.5"D, 115VAC input.	584.44
SMP10PM24P16CB	16 Output Power Supply/Charger - 24VDC @ 10 amp, PTC outputs, AC & battery monitoring, encl. 15.5"H x 12"W x 4.5"D, 115VAC input.	651.78

Multi-Output Power Supply/Chargers with Fire Alarm Interface with Enclosures		
MODEL	DESCRIPTION	PRICE
AL125UL	2 Output Power Supply/Charger w/Fire Alarm Disconnect - 12VDC or 24VDC @ 1 amp, Class 2 power limited outputs, encl. 8.5"H x 7.5"W x 3.5"D, 115VAC input, UL Listed (UL294), cUL Listed.	132.33
AL125ULX	2 Output Power Supply/Charger w/Fire Alarm Disconnect - 12VDC or 24VDC @ 1 amp, Class 2 power limited outputs, encl. 13.5"H x 13"W x 3.25"D., 115VAC input, UL Listed (UL294), cUL Listed.	146.67
AL125ULE	2 Output Power Supply/Charger w/Fire Alarm Disconnect - 12VDC @ 1 amp or 24VDC @ .5 amp, Class 2 power limited outputs, encl. 8.5"H x 7.5"W x 3.5"D, 115VAC input, UL Listed (UL294), cUL Listed.	100.67
AL125ULP	2 Output Power Supply/Charger w/Fire Alarm Disconnect - 12VDC @ 1 amp or 24VDC @ .5 amp, Class 2 power limited outputs, encl. 8.5"H x 7.5"W x 3.5"D, 115VAC input (Includes TP2440 plug-in xfmr), UL Listed (UL294), cUL Listed.	130.00
AL175UL	2 Output Power Supply/Charger w/Fire Alarm Disconnect - 12VDC or 24VDC @ 1.75 amp, Class 2 power limited outputs, encl. 8.5"H x 7.5"W x 3.5"D, 115VAC input, UL Listed (UL294), cUL Listed.	166.67
AL175ULX	2 Output Power Supply/Charger w/Fire Alarm Disconnect - 12VDC or 24VDC @ 1.75 amp, Class 2 power limited outputs, encl. 13.5"H x 13"W x 3.25"D., 115VAC input, UL Listed (UL294), cUL Listed.	188.89
AL175ULX2	2 Class 2 power limited outputs, 12VDC or 24VDC @ 1.75 amp, fire alarm disconnect, Reset switch, encl. 15.5"H x 12"W x 4.5"D, 115VAC input, UL Listed (UL294), cUL Listed.	266.67
AL300ULM	5 Output Power Supply/Charger w/Fire Alarm Disconnect - 12VDC or 24VDC @ 2.5 amp, PTC Class 2 power limited outputs, encl. 13.5"H x 13"W x 3.25"D., 115VAC input, UL Listed (UL294/UL603/UL1069/UL1481), cUL Listed, MEA & CSFM Approved.	309.44
AL300ULMR	5 Output Power Supply/Charger w/Fire Alarm Disconnect - 12VDC or 24VDC @ 2.5 amp, PTC Class 2 power limited outputs, red encl. 13.5"H x 13"W x 3.25"D., 115VAC input, UL Listed (UL294/UL603/UL1069/UL1481), cUL Listed, MEA & CSFM Approved.	309.44
AL400ULM	5 Output Power Supply/Charger w/Fire Alarm Disconnect - 12VDC @ 4 amp or 24VDC @ 3 amp, PTC Class 2 power limited outputs, encl. 13.5"H x 13"W x 3.25"D., 115VAC input, UL Listed (UL294/UL603/UL1069/UL1481), cUL Listed, MEA & CSFM Approved.	368.89
AL400ULMR	5 Output Power Supply/Charger w/Fire Alarm Disconnect - 12VDC @ 4 amp or 24VDC @ 3 amp, PTC Class 2 power limited outputs, red encl. 13.5"H x 13"W x 3.25"D., 115VAC input, UL Listed (UL294/UL603/UL1069/UL1481), cUL Listed, MEA & CSFM Approved.	368.89
AL600ULM	5 Output Power Supply/Charger w/Fire Alarm Disconnect - 12VDC or 24VDC @ 6 amp, PTC Class 2 power limited outputs, encl. 13.5"H x 13"W x 3.25"D., 115VAC input, UL Listed (UL294/UL1481), cUL Listed, MEA & CSFM Approved.	500.00
AL600ULMR	5 Output Power Supply/Charger w/Fire Alarm Disconnect - 12VDC or 24VDC @ 6 amp, PTC Class 2 power limited outputs, red encl. 13.5"H x 13"W x 3.25"D., 115VAC input, UL Listed (UL294/UL1481), cUL Listed, MEA & CSFM Approved.	500.00
AL1012ULM	5 Output Power Supply/Charger w/Fire Alarm Disconnect - 12VDC @ 10 amp, PTC Class 2 power limited outputs, encl. 13.5"H x 13"W x 3.25"D., 115VAC input, UL Listed (UL294), cUL Listed.	533.33
AL1024ULM	5 Output Power Supply/Charger w/Fire Alarm Disconnect - 24VDC @ 10 amp, PTC Class 2 power limited outputs, encl. 13.5"H x 13"W x 3.25"D., 115VAC input, UL Listed (UL294/UL1481), cUL Listed, CSFM & MEA Approved.	622.22
AL1024ULMR	5 Output Power Supply/Charger w/Fire Alarm Disconnect - 24VDC @ 10 amp, PTC Class 2 power limited outputs, red encl. 13.5"H x 13"W x 3.25"D., 115VAC input, UL Listed (UL294/UL1481), cUL Listed, CSFM & MEA Approved.	622.22

UL Listed Triple Voltage Power Supply/Chargers with Enclosures		
MODEL	DESCRIPTION	PRICE
AL400UL3	Triple Voltage Power Supply/Charger - 5VDC & 12VDC @ 1.75 amp & 24VDC @ 1.5 amp, Class 2 power limited outputs, AC & battery monitoring, encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL294/UL603/UL1069/UL1481), cUL Listed, CSFM & MEA Approved.	392.22
AL400UL3X	Triple Voltage Power Supply/Charger - 5VDC & 12VDC @ 1.75 amp & 24VDC @ 1.5 amp, Class 2 power limited outputs, AC & battery monitoring, encl. 15.5"H x 12"W x 4.5"D, 115VAC input, UL Listed (UL294/UL603/UL1069/UL1481), cUL Listed, CSFM & MEA Approved..	414.44
AL600UL3	Triple Voltage Power Supply/Charger - Class 2 power limited outputs 5VDC & 12VDC @ 1.75 amp & 24VDC @ 3 amp non power limited output, AC & battery monitoring, encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL294/UL1481), cUL Listed, CSFM & MEA Approved.	522.22
AL600UL3X	Triple Voltage Power Supply/Charger - Class 2 power limited outputs 5VDC & 12VDC @ 1.75 amp & 24VDC @ 3 amp non power limited output, AC & battery monitoring, encl. 15.5"H x 12"W x 4.5"D, 115VAC input, UL Listed (UL294/UL1481), cUL Listed, CSFM & MEA Approved.	544.44
Access Power Controllers (Fused)		
MODEL	DESCRIPTION	PRICE
AL400ULACM	Power Supply/Charger with Access power controller - 8 fused Class 2 power limited outputs provide 12VDC @ 4 amp or 24VDC @ 3 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation or as dry form "C" contacts, fire alarm disconnect is selectable by output, AC & battery monitoring, encl. 15.5"H x 12"W x 4.5"D, 115VAC input, UL Listed (UL294), cUL Listed, CSFM & MEA Approved.	394.44
AL400ULACMJ	Power Supply/Charger with Access power controller - 8 fused Class 2 power limited outputs provide 12VDC @ 4 amp or 24VDC @ 3 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation or as dry form "C" contacts, fire alarm disconnect is selectable by output, AC & battery monitoring, encl. 18"H x 14.5"W x 4.625"D, 115VAC input, UL Listed (UL294), cUL Listed.	421.11
AL600ULACM	Power Supply/Charger with Access power controller - 8 fused non-power limited outputs provide 12VDC or 24VDC @ 6 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation or as dry form "C" contacts, fire alarm disconnect is selectable by output, AC & battery monitoring, encl. 15.5"H x 12"W x 4.5"D, 115VAC input, UL Listed (UL294), cUL Listed, CSFM & MEA Approved.	524.44
AL600ULACMJ	Power Supply/Charger with Access power controller - 8 fused non-power limited outputs provide 12VDC or 24VDC @ 6 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation or as dry form "C" contacts, fire alarm disconnect is selectable by output, AC & battery monitoring, encl. 18"H x 14.5"W x 4.625"D, 115VAC input, UL Listed (UL294), cUL Listed.	551.11
AL1012ULACM	Power Supply/Charger with Access power controller - 8 fused non-power limited outputs provide 12VDC @ 10 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation or as dry form "C" contacts, fire alarm disconnect is selectable by output, AC & battery monitoring, encl. 15.5"H x 12"W x 4.5"D, 115VAC input, UL Listed (UL294), cUL Listed.	557.78
AL1012ULACMJ	Power Supply/Charger with Access power controller - 8 fused non-power limited outputs provide 12VDC @ 10 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation or as dry form "C" contacts, fire alarm disconnect is selectable by output, AC & battery monitoring, encl. 18"H x 14.5"W x 4.625"D, 115VAC input, UL Listed (UL294), cUL Listed.	584.44
AL1024ULACM	Power Supply/Charger with Access power controller - 8 fused non-power limited outputs provide 24VDC @ 10 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation or as dry form "C" contacts, fire alarm disconnect is selectable by output, AC & battery monitoring, encl. 15.5"H x 12"W x 4.5"D, 115VAC input, UL Listed (UL294), cUL Listed, CSFM & MEA Approved.	646.67
AL1024ULACMJ	Power Supply/Charger with Access power controller - 8 fused non-power limited outputs provide 24VDC @ 10 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation or as dry form "C" contacts, fire alarm disconnect is selectable by output, AC & battery monitoring, encl. 18"H x 14.5"W x 4.625"D, 115VAC input, UL Listed (UL294), cUL Listed.	673.33

Access Power Controllers (PTCs)		
MODEL	DESCRIPTION	PRICE
AL400ULACMCB	Power Supply/Charger with Access power controller - 8 PTC Class 2 power limited outputs provide 12VDC @ 4 amp or 24VDC @ 3 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation, fire alarm disconnect is selectable by output, AC & battery monitoring, encl. 15.5"H x 12"W x 4.5"D, 115VAC input, UL Listed (UL294), cUL Listed, CSFM & MEA Approved.	394.44
AL400ULACMCBJ	Power Supply/Charger with Access power controller - 8 PTC Class 2 power limited outputs provide 12VDC @ 4 amp or 24VDC @ 3 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation, fire alarm disconnect is selectable by output, AC & battery monitoring, encl. 18"H x 14.5"W x 4.625"D, 115VAC input, UL Listed (UL294), cUL Listed.	421.11
AL600ULACMCB	Power Supply/Charger with Access power controller - 8 PTC Class 2 power limited outputs provide 12VDC or 24VDC @ 6 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation, fire alarm disconnect is selectable by output, AC & battery monitoring, encl. 15.5"H x 12"W x 4.5"D, 115VAC input, UL Listed (UL294), cUL Listed, CSFM & MEA Approved.	524.44
AL600ULACMCBJ	Power Supply/Charger with Access power controller - 8 PTC Class 2 power limited outputs provide 12VDC or 24VDC @ 6 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation, fire alarm disconnect is selectable by output, AC & battery monitoring, encl. 18"H x 14.5"W x 4.625"D, 115VAC input, UL Listed (UL294), cUL Listed.	551.11
AL1012ULACMCB	Power Supply/Charger with Access power controller - 8 PTC Class 2 power limited outputs provide 12VDC @ 10 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation, fire alarm disconnect is selectable by output, AC & battery monitoring, encl. 15.5"H x 12"W x 4.5"D, 115VAC input, UL Listed (UL294), cUL Listed.	557.78
AL1012ULACMCBJ	Power Supply/Charger with Access power controller - 8 PTC Class 2 power limited outputs provide 12VDC @ 10 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation, fire alarm disconnect is selectable by output, AC & battery monitoring, encl. 18"H x 14.5"W x 4.625"D, 115VAC input, UL Listed (UL294), cUL Listed.	584.44
AL1024ULACMCB	Power Supply/Charger with Access power controller - 8 PTC Class 2 power limited outputs provide 24VDC @ 10 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation, fire alarm disconnect is selectable by output, AC & battery monitoring, encl. 15.5"H x 12"W x 4.5"D, 115VAC input, UL Listed (UL294), cUL Listed, CSFM & MEA Approved.	646.67
AL1024ULACMCBJ	Power Supply/Charger with Access power controller - 8 PTC Class 2 power limited outputs provide 24VDC @ 10 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation, fire alarm disconnect is selectable by output, AC & battery monitoring, encl. 18"H x 14.5"W x 4.625"D, 115VAC input, UL Listed (UL294), cUL Listed.	673.33
Distributed Control Panel Power Units		
MODEL	DESCRIPTION	PRICE
AL168CB	8 Output Control Panel Power Supply - 16VAC @ 6 amp or 18VAC @ 5 amp, PTC outputs, encl. 8.5"H x 7.5"W x 3.5"D, 115VAC input.	200.00
AL168175CB	8 Output Control Panel Power Supply - 16VAC @ 10 amp, PTC outputs, encl. 8.5"H x 7.5"W x 3.5"D, 115VAC input.	217.78
AL168300CB	8 Output Control Panel Power Supply - 16VAC @ 18 amp or 18VAC @ 16 amp, PTC outputs, encl. 13.5"H x 13"W x 3.25"D, 115VAC input.	266.67
AL168300CBM	8 Output Control Panel Power Supply - 16VAC @ 18 amp or 18VAC @ 16 amp, PTC outputs, encl. 8.5"H x 7.5"W x 3.75"D, 115VAC input.	255.56
AL168600CB	8 Output Control Panel Power Supply - 16VAC @ 36 amp or 18VAC @ 32 amp, PTC outputs, encl. 13.5"H x 13"W x 3.25"D, 115VAC input.	288.89

MAXIMAL - Access Power Controllers (Fused)		
MODEL	DESCRIPTION	PRICE
MAXIMAL3	Power Supply/Charger with Access power controllers - 16 fused non-power limited outputs, 16 outputs can be selected for 12VDC or 24VDC @ 5.5 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation or as dry form "C" contacts, fire alarm disconnect is selectable by output, AC & battery monitoring, encl. 26"H x 19"W x 6.25"D, 115VAC input, Accommodates up to 4 - 12VDC/12AH batteries, UL Listed (UL294), cUL Listed, CSFM Approved.	692.22
MAXIMAL5	Power Supply/Charger with Access power controllers - 16 fused non-power limited outputs, 16 outputs are 12VDC @ 9 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation or as dry form "C" contacts, fire alarm disconnect is selectable by output, AC & battery monitoring, encl. 26"H x 19"W x 6.25"D, 115VAC input, Accommodates up to 4 - 12VDC/12AH batteries, UL Listed (UL294), cUL Listed, CSFM Approved.	736.67
MAXIMAL7	Power Supply/Charger with Access power controllers - 16 fused non-power limited outputs, 16 outputs are 24VDC @ 9.4 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation or as dry form "C" contacts, fire alarm disconnect is selectable by output, AC & battery monitoring, encl. 26"H x 19"W x 6.25"D, 115VAC input, Accommodates up to 4 - 12VDC/12AH batteries, UL Listed (UL294), cUL Listed, CSFM Approved.	781.11
MAXIMAL11	2 Power Supply/Chargers with Access power controllers - 16 fused Class 2 power limited outputs, each set of 8 outputs are selectable for 12VDC @ 3.5 amp or 24VDC @ 2.7 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation or as dry form "C" contacts, fire alarm disconnect is selectable by output, AC & battery monitoring, encl. 26"H x 19"W x 6.25"D, 115VAC input, Accommodates up to 4 - 12VDC/12AH batteries, UL Listed (UL294), cUL Listed, CSFM Approved.	777.78
MAXIMAL33	2 Power Supply/Chargers with Access power controllers - 16 fused non-power limited outputs, each set of 8 outputs are selectable for 12VDC @ 5.5 amp or 24VDC @ 5.7 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation or as dry form "C" contacts, fire alarm disconnect is selectable by output, AC & battery monitoring, encl. 26"H x 19"W x 6.25"D, 115VAC input, Accommodates up to 4 - 12VDC/12AH batteries, UL Listed (UL294), cUL Listed, CSFM Approved.	1025.56
MAXIMAL55	2 Power Supply/Chargers with Access power controllers - 16 fused non-power limited outputs, each set of 8 outputs is 12VDC @ 9.5 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation or as dry form "C" contacts, fire alarm disconnect is selectable by output, AC & battery monitoring, encl. 26"H x 19"W x 6.25"D, 115VAC input, Accommodates up to 4 - 12VDC/12AH batteries, UL Listed (UL294), cUL Listed, CSFM Approved.	1114.44
MAXIMAL77	2 Power Supply/Charger with Access power controllers - 16 fused non-power limited outputs, each set of 8 outputs is 24VDC @ 9.7 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation or as dry form "C" contacts, fire alarm disconnect is selectable by output, AC & battery monitoring, encl. 26"H x 19"W x 6.25"D, 115VAC input, Accommodates up to 4 - 12VDC/12AH batteries, UL Listed (UL 294), cUL Listed, CSFM Approved.	1203.33
MAXIMAL75	2 Power Supply/Charger with Access power controllers - 16 fused non-power limited outputs, 8 outputs are 12VDC @ 9.5 amp and 8 outputs are 24VDC @ 9.7 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation or as dry form "C" contacts, fire alarm disconnect is selectable by output, AC & battery monitoring, encl. 26"H x 19"W x 6.25"D, 115VAC input, Accommodates up to 4 - 12VDC/12AH batteries, UL Listed (UL294), cUL Listed, CSFM Approved.	1158.89

MAXIMAL - Access Power Controllers (PTCs)		
MODEL	DESCRIPTION	PRICE
MAXIMAL3D	Power Supply/Charger with Access power controllers - 16 PTC Class 2 power limited outputs, 16 outputs can be selected for 12VDC or 24VDC @ 5.5 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation, fire alarm disconnect is selectable by output, AC & battery monitoring, encl. 26"H x 19"W x 6.25"D, 115VAC input, Accommodates up to 4 - 12VDC/12AH batteries, UL Listed (UL294), cUL Listed, CSFM Approved.	692.22
MAXIMAL5D	Power Supply/Charger with Access power controllers - 16 PTC Class 2 power limited outputs, 16 outputs are 12VDC @ 9 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation, fire alarm disconnect is selectable by output, AC & battery monitoring, encl. 26"H x 19"W x 6.25"D, 115VAC input, Accommodates up to 4 - 12VDC/12AH batteries, UL Listed (UL294), cUL Listed, CSFM Approved.	736.67
MAXIMAL7D	Power Supply/Charger with Access power controllers - 16 PTC Class 2 power limited outputs, 16 outputs are 24VDC @ 9.4 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation, fire alarm disconnect is selectable by output, AC & battery monitoring, encl. 26"H x 19"W x 6.25"D, 115VAC input, Accommodates up to 4 - 12VDC/12AH batteries, UL Listed (UL294), cUL Listed, CSFM Approved.	781.11
MAXIMAL11D	2 Power Supply/Charger with Access power controllers - 16 PTC Class 2 power limited outputs, each set of 8 outputs are selectable for 12VDC @ 3.5 amp or 24VDC @ 2.7 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation, fire alarm disconnect is selectable by output, AC & battery monitoring, encl. 26"H x 19"W x 6.25"D, 115VAC input, Accommodates up to 4 - 12VDC/12AH batteries, UL Listed (UL294), cUL Listed, CSFM Approved.	777.78
MAXIMAL33D	2 Power Supply/Charger with Access power controllers - 16 PTC Class 2 power limited outputs, each set of 8 outputs are selectable for 12VDC @ 5.5 amp or 24VDC @ 5.7 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation, fire alarm disconnect is selectable by output, AC & battery monitoring, encl. 26"H x 19"W x 6.25"D, 115VAC input, Accommodates up to 4 - 12VDC/12AH batteries, UL Listed (UL294), cUL Listed, CSFM Approved.	1025.56
MAXIMAL55D	2 Power Supply/Charger with Access power controllers - 16 PTC power limited outputs, each set of 8 outputs is 12VDC @ 9.5 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation, fire alarm disconnect is selectable by output, AC & battery monitoring, encl. 26"H x 19"W x 6.25"D, 115VAC input, Accommodates up to 4 - 12VDC/12AH batteries, UL Listed (UL294), cUL Listed, CSFM Approved.	1114.44
MAXIMAL77D	2 Power Supply/Charger with Access power controllers - 16 PTC Class 2 power limited outputs, each set of 8 outputs is 24VDC @ 9.7 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation, fire alarm disconnect is selectable by output, AC & battery monitoring, encl. 26"H x 19"W x 6.25"D, 115VAC input, Accommodates up to 4 - 12VDC/12AH batteries, UL Listed (UL294), cUL Listed, CSFM Approved.	1203.33
MAXIMAL75D	2 Power Supply/Charger with Access power controllers - 16 PTC Class 2 power limited outputs, 8 outputs are 12VDC @ 9.5 amp and 8 outputs are 24VDC @ 9.7 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation, fire alarm disconnect is selectable by output, AC & battery monitoring, encl. 26"H x 19"W x 6.25"D, 115VAC input, Accommodates up to 4 - 12VDC/12AH batteries, UL Listed (UL294), cUL Listed, CSFM Approved.	1158.89

MAXIMAL - Expandable Access Power Systems		
MODEL	DESCRIPTION	PRICE
MAXIMAL11E	2 Power Supply/Chargers - Each are selectable for 12VDC @ 4 amp or 24VDC @ 3 amp, Class 2 power limited outputs, AC & battery monitoring, encl. 26"H x 19"W x 6.25"D accommodates a variety of Altronix modules for power distribution & control, Accommodates up to 4 - 12VDC/12AH batteries, 115VAC input, UL Listed (UL294), cUL Listed, CSFM Approved.	607.78
MAXIMAL13E	2 Power Supply/Chargers - One is selectable for 12VDC @ 4 amp or 24VDC @ 3 amp Class 2 power limited output and One is selectable for 12VDC or 24VDC @ 6 amp non-power limited output, AC & battery monitoring, encl. 26"H x 19"W x 6.25"D accommodates a variety of Altronix modules for power distribution & control, Accommodates up to 4 - 12VDC/12AH batteries, 115VAC input, UL Listed (UL294), cUL Listed, CSFM Approved.	733.33
MAXIMAL33E	2 Power Supply/Chargers - Each are selectable for 12VDC or 24VDC @ 6 amp, non-power limited outputs, AC & battery monitoring, encl. 26"H x 19"W x 6.25"D accommodates a variety of Altronix modules for power distribution & control, Accommodates up to 4 - 12VDC/12AH batteries, 115VAC input, UL Listed (UL294), cUL Listed, CSFM Approved.	855.56
MAXIMAL35E	2 Power Supply/Chargers - One is selectable for 12VDC or 24VDC @ 6 amp and One is selectable for 12VDC @ 10 amp, non-power limited outputs, AC & battery monitoring, encl. 26"H x 19"W x 6.25"D accommodates a variety of Altronix modules for power distribution & control, Accommodates up to 4 - 12VDC/12AH batteries, 115VAC input, UL Listed (UL294), cUL Listed, CSFM Approved.	900.00
MAXIMAL37E	2 Power Supply/Chargers - One is selectable for 12VDC or 24VDC @ 6 amp and one is 24VDC @ 10 amp, non-power limited outputs, AC & battery monitoring, encl. 26"H x 19"W x 6.25"D accommodates a variety of Altronix modules for power distribution & control, Accommodates up to 4 - 12VDC/12AH batteries, 115VAC input, UL Listed (UL294), cUL Listed, CSFM Approved.	944.44
MAXIMAL55E	2 Power Supply/Chargers - Each are 12VDC @ 10 amp, non-power limited outputs, AC & battery monitoring, encl. 26"H x 19"W x 6.25"D accommodates a variety of Altronix modules for power distribution & control, Accommodates up to 4 - 12VDC/12AH batteries, 115VAC input, UL Listed (UL294), cUL Listed, CSFM Approved.	944.44
MAXIMAL77E	2 Power Supply/Chargers - Each are 24VDC @ 10 amp, non-power limited outputs, AC & battery monitoring, encl. 26"H x 19"W x 6.25"D accommodates a variety of Altronix modules for power distribution & control, Accommodates up to 4 - 12VDC/12AH batteries, 115VAC input, UL Listed (UL294), cUL Listed, CSFM Approved.	1033.33
MAXIMAL75E	2 Power Supply/Chargers - One is 12VDC @ 10 amp and one is 24VDC @ 10 amp, non-power limited outputs, AC & battery monitoring, encl. 26"H x 19"W x 6.25"D accommodates a variety of Altronix modules for power distribution & control, Accommodates up to 4 - 12VDC/12AH batteries, 115VAC input, UL Listed (UL294), cUL Listed.	988.89
Rack Mount Multi-Output Power Supply/Charger (PTCs)		
MODEL	DESCRIPTION	PRICE
R1224DC16CB	16 Output Power Supply/Charger - 12VDC or 24VDC @ 4.5 amp per bank of 4 outputs, 18 amp total supply current, PTC Class 2 power limited outputs, 2U EIA 19" Rack Mount Chassis, 115VAC input, UL Listed (UL1012), cUL Listed.	677.78

MAXIMAL Access Power Controllers Rack Mount (Fused)		
MODEL	DESCRIPTION	PRICE
MAXIMAL1RH	Power Supply/Charger with Access power controllers - 8 fused outputs are selectable for 12VDC @ 4 amp or 24VDC @ 3 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation or as dry form "C" contacts, fire alarm disconnect is selectable by output, AC & battery monitoring, 2U EIA 19" Rack Mount Chassis, 115VAC input.	513.33
MAXIMAL1R	Power Supply/Charger with Access power controllers - 16 fused outputs are selectable for 12VDC @ 4 amp or 24VDC @ 3 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation or as dry form "C" contacts, fire alarm disconnect is selectable by output, AC & battery monitoring, 2U EIA 19" Rack Mount Chassis, 115VAC input.	581.11
MAXIMAL3RH	Power Supply/Charger with Access power controllers - 8 fused outputs are selectable for 12VDC or 24VDC @ 6 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation or as dry form "C" contacts, fire alarm disconnect is selectable by output, AC & battery monitoring, 2U EIA 19" Rack Mount Chassis, 115VAC input.	557.78
MAXIMAL3R	Power Supply/Charger with Access power controllers - 16 fused outputs are selectable for 12VDC or 24VDC @ 6 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation or as dry form "C" contacts, fire alarm disconnect is selectable by output, AC & battery monitoring, 2U EIA 19" Rack Mount Chassis, 115VAC input.	625.56
MAXIMAL33R	2 Power Supply/Chargers with Access power controllers - 16 fused outputs, each set of 8 outputs are selectable for 12VDC or 24VDC @ 6 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation or as dry form "C" contacts, fire alarm disconnect is selectable by output, AC & battery monitoring, 2U EIA 19" Rack Mount Chassis, 115VAC input.	936.67

MAXIMAL Access Power Controllers Rack Mount (PTCs)		
MODEL	DESCRIPTION	PRICE
MAXIMAL1RHD	Power Supply/Charger with Access power controllers - 8 PTC outputs are selectable for 12VDC @ 4 amp or 24VDC @ 3 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation, fire alarm disconnect is selectable by output, AC & battery monitoring, 2U EIA 19" Rack Mount Chassis, 115VAC input.	513.33
MAXIMAL1RD	Power Supply/Charger with Access power controllers - 16 PTC outputs are selectable for 12VDC @ 4 amp or 24VDC @ 3 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation, fire alarm disconnect is selectable by output, AC & battery monitoring, 2U EIA 19" Rack Mount Chassis, 115VAC input.	581.11
MAXIMAL3RHD	Power Supply/Charger with Access power controllers - 8 PTC outputs are selectable for 12VDC or 24VDC @ 6 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation, fire alarm disconnect is selectable by output, AC & battery monitoring, 2U EIA 19" Rack Mount Chassis, 115VAC input.	557.78
MAXIMAL3RD	Power Supply/Charger with Access power controllers - 16 PTC outputs are selectable for 12VDC or 24VDC @ 6 amp, outputs are individually selectable for Fail-Safe or Fail-Secure operation, fire alarm disconnect is selectable by output, AC & battery monitoring, 2U EIA 19" Rack Mount Chassis, 115VAC input.	625.56
MAXIMAL33RD	2 Power Supply/Chargers with Access power controllers - 16 PTC outputs, each set of 8 outputs are selectable for 12VDC or 24VDC @ 6 amp (12 amp max.), outputs are individually selectable for Fail-Safe or Fail-Secure operation, fire alarm disconnect is selectable by output, AC & battery monitoring, 2U EIA 19" Rack Mount Chassis, 115VAC input.	936.67

Strikelt - Panic Device Power Controllers		
MODEL	DESCRIPTION	PRICE
Strikelt1	Dual Panic Device Power Controller - Independently or simultaneously controlled lock outputs for two 24VDC panic hardware devices with high inrush current requirements. Programmable 1 to 30 sec. timed lock release, Two follower relay outputs, Two delayed momentary relay outputs, One 12VDC & One 24VDC aux. power outputs rated @ 1 amp each, Fire Alarm disconnect, built-in battery charger, encl: 13.5"H x 13"W x 3.25"D, Accommodates up to 2 - 12VDC/7AH batteries, 115VAC input, UL Listed (UL294), cUL Listed. MEA & CSFM Approved.	522.22
Strikelt2	Panic Device Power Controller - Controlled lock output for 24VDC panic hardware device with high inrush current requirements or a mag lock/electric strike, One 24VDC aux. power output rated @ 0.5 amp, built-in battery charger, encl. 8.5"H x 7.5"W x 3.5"D, Accommodates up to 2 - 12VDC/4AH batteries, 115VAC input. UL Listed (UL294), cUL Listed.	288.89

Rack Mount Power Supplies DC (PTCs)		
MODEL	DESCRIPTION	PRICE
VertiLine3D	8 Output Rack Mount Power Supply - 12VDC @ 8 amp, PTC outputs, 1U EIA 19" Rack Mount Chassis, 115VAC input	367.78
VertiLine6D	8 Output Rack Mount Power Supply - 24VDC @ 8 amp, PTC outputs, 1U EIA 19" Rack Mount Chassis, 115VAC input	367.78
VertiLine33D	16 Output Rack Mount Power Supply - 12VDC @ 8 amp, PTC outputs, 1U EIA 19" Rack Mount Chassis, 115VAC input	400.00
VertiLine33TD	16 Output Rack Mount Power Supply - 12VDC @ 16 amp, PTC outputs, 1U EIA 19" Rack Mount Chassis, 115VAC input	517.78
VertiLine63D	16 Output Rack Mount Power Supply - 24VDC @ 8 amp, PTC outputs, 1U EIA 19" Rack Mount Chassis, 115VAC input	400.00
VertiLine63TD	16 Output Rack Mount Power Supply - 24VDC @ 16 amp, PTC outputs, 1U EIA 19" Rack Mount Chassis, 115VAC input	517.78
NAC Power Extenders		
MODEL	DESCRIPTION	PRICE
AL602ULADA	NAC Power Extender - 24VDC @ 6.5 amp, 2 - Class A or 4 - Class B NAC circuits, operates 2-wire Horn/Strobes, generates System Sensor, Gentex, Faraday & Amseco sync protocols, 1 amp aux. output, red encl. 15.5"H x 12"W x 4.5"D, 115VAC input, UL Listed Fire (UL864/UL1481), MEA, CSFM & FM Approved.	466.67
AL602ULADAJ	NAC Power Extender - 24VDC @ 6.5 amp, 2 - Class A or 4 - Class B NAC circuits, operates 2-wire Horn/Strobes, generates System Sensor, Gentex, Faraday & Amseco sync protocols, 1 amp aux. output, red encl. 18"H x 14.5"W x 4.625"D, 115VAC input, UL Listed Fire (UL864/UL1481), MEA, CSFM Approved.	493.33
AL642ULADA	NAC Power Extender - 24VDC @ 6.5 amp. 4 - Class A or 4 - Class B NAC circuits, operates 2-wire Horn/Strobes, generates System Sensor, Gentex, Faraday & Amseco sync protocols, two - 1 amp aux. outputs, red encl. 18"H x 14.5"W x 4.625"D, 115VAC input, UL Listed Fire (UL864/UL1481) MEA, CSFM & FM Approved.	611.11
AL802ULADA	NAC Power Extender - 24VDC @ 8 amp. 2 - Class A or 4 - Class B NAC circuits, operates 2-wire Horn/Strobes, generates System Sensor, Gentex, Faraday & Amseco sync protocols, 1 amp aux. output, red encl. 15.5"H x 12"W x 4.5"D, 115VAC input, UL Listed Fire (UL864/UL1481), MEA, CSFM & FM Approved.	540.73
AL802ULADAJ	NAC Power Extender - 24VDC @ 8 amp. 2 - Class A or 4 - Class B NAC circuits, operates 2-wire Horn/Strobes, generates System Sensor, Gentex, Faraday & Amseco sync protocols, 1 amp aux. output, red encl. 18"H x 14.5"W x 4.625"D, 115VAC input, UL Listed Fire (UL864/UL1481), MEA, CSFM Approved.	567.40
AL842ULADA	NAC Power Extender - 24VDC @ 8 amp. 4 - Class A or 4 - Class B NAC circuits, operates 2-wire Horn/Strobes. Generates System Sensor, Gentex, Faraday & Amseco sync protocols, two - 1 amp aux. output, red encl. 18"H x 14.5"W x 4.625"D, 115VAC input, UL Listed Fire (UL864/UL1481) MEA, CSFM & FM Approved.	666.67
AL1002ULADA	NAC Power Extender - 24VDC @ 10 amp. 2 - Class A or 4 - Class B NAC circuits, operates 2-wire Horn/Strobes, generates Cooper/Wheelock, System Sensor, Gentex, Faraday & Amseco sync protocols, 1 amp aux. output, red encl. 15.5"H x 12"W x 4.5"D, 115VAC input, UL Listed (UL864), MEA, CSFM & FM Approved.	611.11
AL1002ULADAJ	NAC Power Extender - 24VDC @ 10 amp. 2 - Class A or 4 - Class B NAC circuits, operates 2-wire Horn/Strobes, generates Cooper/Wheelock, System Sensor, Gentex, Faraday & Amseco sync protocols, two - 1 amp aux. output, red encl. 18"H x 14.5"W x 4.625"D, 115VAC input, UL Listed (UL864), MEA, CSFM Approved.	637.78
AL1042ULADA	NAC Power Extender - 24VDC @ 10 amp. 4 - Class A or 4 - Class B NAC circuits, operates 2-wire Horn/Strobes, generates Cooper/Wheelock, System Sensor, Gentex, Faraday & Amseco sync protocols, two - 1 amp aux. outputs, red encl. 18"H x 14.5"W x 4.625"D, 115VAC input, UL Listed (UL864) MEA, CSFM & FM Approved.	700.00

Power over the Ethernet		
MODEL	DESCRIPTION	PRICE
NetWay1	Single Port Midspan PoE Injector 24VAC/24VDC operation - PoE compliant port is rated @ 15.4W IEEE 802.3af, PoE shutdown feature, compact insulated housing, UL/cUL Listed (UL60950-1), UL Listed (UL294), CE approved.	71.11
NetWay1P	Single Port Midspan Injector - One PoE compliant port rated @ 15.4W IEEE 802.3af, PoE shutdown feature, compact insulated housing, UL/cUL Listed (UL60950-1), UL Listed (UL294). Includes TP2440 Plug-in transformer 24VAC/40VA, 115VAC input, UL Listed.	91.11
NetWay112	Single Port Midspan PoE Injector 12VDC operation - PoE compliant port is rated @ 15.4W IEEE 802.3af, PoE shutdown feature, compact insulated housing, CE approved.	71.11
NetWay1E	Single Port Midspan Injector - Single port provides PoE per IEEE 802.3af or PoE+ per IEEE 802.3at, PoE shutdown feature, 115VAC Input, UL/cUL Listed (UL60950-1). CE Approved.	333.33
NetWay1EV	Single Port Midspan Injector - Single port provides PoE per IEEE 802.3af or PoE+ per IEEE 802.3at, PoE shutdown feature, 230VAC Input, UL/cUL Listed (UL60950-1). CE Approved.	333.33
NetWay8	8 Port Midspan - each port provides PoE per IEEE 802.3af or PoE+ per IEEE 802.3at. Total power 150W, 1U EIA 19" Rack Mount Chassis, 115VAC Input. UL/CUL Listed (UL 609050-1)	547.78
NetWay16	16 Port Midspan - each port provides PoE per IEEE 802.3af or PoE+ per IEEE 802.3at. Total power 300W, 1U EIA 19" Rack Mount Chassis, 115VAC Input. UL/CUL Listed (UL 609050-1)	921.11
NetWay8M	8 Port Managed Midspan - each port provides PoE per IEEE 802.3af or PoE+ per IEEE 802.3at. Total power 150W, PoE shutdown selectable by port, Ethernet port facilitates programming and status monitoring via laptop or LAN, 1U EIA 19" Rack Mount Chassis, 115VAC Input, UL/cUL Listed (UL60950-1), UL Listed (UL294) .	592.22
NetWay16M	16 Port Managed Midspan - each port provides PoE per IEEE 802.3af or PoE+ per IEEE 802.3at. Total power 300W, PoE shutdown selectable by port, Ethernet port facilitates programming and status monitoring via laptop or LAN, 1U EIA 19" Rack Mount Chassis, 115VAC Input, UL/cUL Listed (UL60950-1), UL Listed (UL294).	987.78
NetWay1512	12VDC/13W NetWay midspan adapter for IP cameras and devices, UL/cUL Listed (UL60950-1).	73.33
NetWay3012	12VDC/30W NetWay midspan adapter for IP cameras and devices, UL/cUL Listed (UL60950-1).	95.56
NetWayXT	Repeater extends ethernet and PoE an additional 100m (328 ft.), UL/cUL Listed (UL60950-1).	158.89
Ethernet over Coax		
MODEL	DESCRIPTION	PRICE
eBridge1CR	Ethernet over coax receiver module. Supports IP video/data over existing coax cable up to 1,500 ft. UL/cUL Listed (UL60950-1), UL Listed (UL294). CE Approved. C-Tick Compliant.	164.80
eBridge1CT	Ethernet over coax transceiver module. Supports IP video/data over existing coax cable up to 2,000 ft. UL/cUL Listed (UL60950-1), UL Listed (UL294). CE Approved. C-Tick Compliant.	164.80
eBridge1CRT	Ethernet over coax kit. Supports IP video/data over existing coax cable up to 2,000 ft. Includes one (1) eBridge1CR receiver and one (1) eBridge1CT transceiver. UL/cUL Listed (UL60950-1), UL Listed (UL294). CE Approved. C-Tick Compliant.	313.11
eBridge4CR	4-Port ethernet over coax receiver. Supports IP video/data over existing coax cable up to 1,500 ft.	795.00
eBridge16CR	16-Port ethernet over coax receiver. Supports IP video/data over existing coax cable up to 1,500 ft.	3390.00
Ethernet and PoE over Coax		
MODEL	DESCRIPTION	PRICE
eBridge1PCR	Ethernet and PoE over coax receiver module. Supports IP video/data/PoE over existing coax cable up to 2,000 ft. UL/cUL Listed (UL60950-1), UL Listed (UL294). CE Approved. C-Tick Compliant.	211.11
eBridge1PCT	Ethernet and PoE over coax transceiver module. Supports IP video/data/PoE over existing coax cable up to 2,000 ft. UL/cUL Listed (UL60950-1), UL Listed (UL294). CE Approved. C-Tick Compliant.	197.78
eBridge1PCRT	Ethernet over coax kit. Supports IP video/data over existing coax cable up to 2,000 ft. Includes one (1) eBridge1PCR receiver and one (1) eBridge1PCT transceiver. UL/cUL Listed (UL60950-1), UL Listed (UL294). CE Approved. C-Tick Compliant.	391.11

8-Channel Passive UTP Transceiver Hubs with Integral Power (115VAC)		
<i>Units with CAT-5 & BNC connectors on rear of unit</i>		
MODEL	DESCRIPTION	PRICE
HubWay8CDS	8 Channel Passive UTP Transceiver Hub with Integral Camera Power, Video/Data up to 750 ft., 5 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115VAC Input, UL Listed (UL2044), cUL Listed.	611.11
HubWay82CDS	8 Channel Passive UTP Transceiver Hub with Integral Camera Power, Video/Data up to 750 ft., 5 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115VAC Input, UL Listed (UL2044), cUL Listed, includes 8 UL Listed Accessory HubWayAv Video Balun/Combiners for 24VAC cameras.	806.67
HubWay83CDS	8 Channel Passive UTP Transceiver Hub with Integral Camera Power, Video/Data up to 750 ft., 5 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115VAC Input, UL Listed (UL2044), cUL Listed, includes 8 UL Listed Accessory HubWayDv Video Balun/Combiners for 12VDC cameras.	897.78
<i>Units with CAT-5 connectors on front & BNC connectors on rear of unit</i>		
MODEL	DESCRIPTION	PRICE
HubWay8CD	8 Channel Passive UTP Transceiver Hub with Integral Camera Power, Video/Data up to 750 ft., 5 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115VAC Input, UL Listed (UL2044), cUL Listed.	611.11
HubWay82CD	8 Channel Passive UTP Transceiver Hub with Integral Camera Power, Video/Data up to 750 ft., 5 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115VAC Input, UL Listed (UL2044), cUL Listed, includes 8 UL Listed Accessory HubWayAv Video Balun/Combiners for 24VAC cameras.	806.67
HubWay83CD	8 Channel Passive UTP Transceiver Hub with Integral Camera Power, Video/Data up to 750 ft., 5 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115VAC Input, UL Listed (UL2044), cUL Listed, includes 8 UL Listed Accessory HubWayDv Video Balun/Combiners for 12VDC cameras.	897.78
8-Channel Passive UTP Transceiver Hubs with Integral Power (115/230VAC)		
<i>Units with CAT-5 & BNC connectors on rear of unit</i>		
MODEL	DESCRIPTION	PRICE
HubWay8DS	8 Channel Passive UTP Transceiver Hub with Integral Camera Power, Video/Data up to 750 ft., 5 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115/230VAC Input, UL Listed (UL2044).	611.11
HubWay82DS	8 Channel Passive UTP Transceiver Hub with Integral Camera Power, Video/Data up to 750 ft., 5 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115/230VAC Input, UL Listed (UL2044), includes 8 UL Listed Accessory HubWayAv Video Balun/Combiners for 24VAC cameras.	806.67
HubWay83DS	8 Channel Passive UTP Transceiver Hub with Integral Camera Power, Video/Data up to 750 ft., 5 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115/230VAC Input, UL Listed (UL2044), includes 8 UL Listed Accessory HubWayDv Video Balun/Combiners for 12VDC cameras.	897.78
<i>Units with CAT-5 connectors on front & BNC connectors on rear of unit</i>		
MODEL	DESCRIPTION	PRICE
HubWay8D	8 Channel Passive UTP Transceiver Hub with Integral Camera Power, Video/Data up to 750 ft., 5 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115/230VAC Input, UL Listed (UL2044).	611.11
HubWay82D	8 Channel Passive UTP Transceiver Hub with Integral Camera Power, Video/Data up to 750 ft., 5 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115/230VAC Input, UL Listed (UL2044), includes 8 UL Listed Accessory HubWayAv Video Balun/Combiners for 24VAC cameras.	806.67
HubWay83D	8 Channel Passive UTP Transceiver Hub with Integral Camera Power, Video/Data up to 750 ft., 5 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115/230VAC Input, UL Listed (UL2044), includes 8 UL Listed Accessory HubWayDv Video Balun/Combiners for 12VDC cameras.	897.78

8-Channel Passive UTP Transceiver Hubs with Integral Isolated Power (115/230VAC)		
<i>Units with CAT-5 connectors on front & BNC connectors on rear of unit</i>		
MODEL	DESCRIPTION	PRICE
HubWay8Di	8 Channel Passive UTP Transceiver Hub with Integral Camera Power, Video/Data up to 750 ft., 8 amp total current, individually selectable 24VAC or 28VAC isolated PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115/230VAC Input, UL Listed (UL2044), cUL Listed.	744.44
HubWay82Di	8 Channel Passive UTP Transceiver Hub with Integral Camera Power, Video/Data up to 750 ft., 8 amp total current, individually selectable 24VAC or 28VAC isolated PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115/230VAC Input, UL Listed (UL2044), cUL Listed, includes 8 UL Listed Accessory HubWayAv Video Balun/Combiners for 24VAC cameras.	940.00
HubWay83Di	8 Channel Passive UTP Transceiver Hub with Integral Camera Power, Video/Data up to 750 ft., 8 amp total current, individually selectable 24VAC or 28VAC isolated PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115/230VAC Input, UL Listed (UL2044), cUL Listed, includes 8 UL Listed Accessory HubWayDv Video Balun/Combiners for 12VDC cameras.	1031.11
16-Channel Passive UTP Transceiver Hubs with Integral Power (115VAC)		
<i>Units with CAT-5 connectors on front & BNC connectors on rear of unit</i>		
MODEL	DESCRIPTION	PRICE
HubWay16CD	16 Channel Passive UTP Transceiver Hub with Integral Camera Power, Video/Data up to 750 ft., 10 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115VAC Input, UL Listed (UL2044), cUL Listed.	1222.22
HubWay162CD	16 Channel Passive UTP Transceiver Hub with Integral Camera Power, Video/Data up to 750 ft., 10 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115VAC Input, UL Listed (UL2044), cUL Listed, includes 16 UL Listed Accessory HubWayAv Video Balun/Combiners for 24VAC cameras.	1620.00
HubWay163CD	16 Channel Passive UTP Transceiver Hub with Integral Camera Power, Video/Data up to 750 ft., 10 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115VAC Input, UL Listed (UL2044), cUL Listed, includes 16 UL Listed Accessory HubWayDv Video Balun/Combiners for 12VDC cameras.	1795.56
16-Channel Passive UTP Transceiver Hubs with Integral Power (115/230VAC)		
<i>Units with CAT-5 connectors on front & BNC connectors on rear of unit</i>		
MODEL	DESCRIPTION	PRICE
HubWay16D	16 Channel Passive UTP Transceiver Hub with Integral Camera Power, Video/Data up to 750 ft., 10 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115/230VAC Input, UL Listed (UL2044).	1222.22
HubWay162D	16 Channel Passive UTP Transceiver Hub with Integral Camera Power, Video/Data up to 750 ft., 10 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115/230VAC Input, UL Listed (UL2044), includes 16 UL Listed Accessory HubWayAv Video Balun/Combiners for 24VAC cameras.	1620.00
HubWay163D	16 Channel Passive UTP Transceiver Hub with Integral Camera Power, Video/Data up to 750 ft., 10 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115/230VAC Input, UL Listed (UL2044), includes 16 UL Listed Accessory HubWayDv Video Balun/Combiners for 12VDC cameras.	1795.56
16-Channel Passive UTP Transceiver Hubs with Integral Isolated Power (115/230VAC)		
<i>Units with CAT-5 connectors on front & BNC connectors on rear of unit</i>		
MODEL	DESCRIPTION	PRICE
HubWay16Di	16 Channel Passive UTP Transceiver Hub with Integral Camera Power, Video/Data up to 750 ft., 16 amp total current, individually selectable 24VAC or 28VAC isolated PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115/230VAC Input, UL Listed (UL2044), cUL Listed.	1488.89
HubWay162Di	16 Channel Passive UTP Transceiver Hub with Integral Camera Power, Video/Data up to 750 ft., 16 amp total current, individually selectable 24VAC or 28VAC isolated PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115/230VAC Input, UL Listed (UL2044), cUL Listed, includes 16 UL Listed Accessory HubWayAv Video Balun/Combiners for 24VAC cameras.	1886.67
HubWay163Di	16 Channel Passive UTP Transceiver Hub with Integral Camera Power, Video/Data up to 750 ft., 16 amp total current, individually selectable 24VAC or 28VAC isolated PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115/230VAC Input, UL Listed (UL2044), cUL Listed, includes 16 UL Listed Accessory HubWayDv Video Balun/Combiners for 12VDC cameras.	2062.22

Passive UTP Transceiver Hub		
<i>Units with CAT-5 connectors on front & BNC connectors on rear of unit</i>		
MODEL	DESCRIPTION	PRICE
HubWayH16	16 Channel Passive UTP Transceiver Hub, allows Video, remote power and PTZ control to be transmitted over a single CAT-5e/6 cable, individual channels are selectable for video/PTZ control/power or video and power only, 1U EIA 19" Rack Mount Chassis	488.89
Active UTP Transceiver Hubs with Automatic Picture & Gain Control (115/230VAC)		
MODEL	DESCRIPTION	PRICE
HubWayEX16	Active UTP Transceiver Hub. Allows video transmission of up to 16 cameras over four (4) Cat 5 cables. Video up to one mile. Automatic Picture and Gain control. 1U EIA 19" Rack Chassis, 115/230VAC Input, UL Listed (UL2044), cUL Listed.	2208.89
HubWayEX32	Active UTP Transceiver Hub. Allows video transmission of up to 32 cameras over eight (8) Cat 5 cables. Video up to one mile. Automatic Picture and Gain control. 1U EIA 19" Rack Chassis, 115/230VAC Input, UL Listed (UL2044), cUL Listed.	4333.33
HubWayEX16S	16 Port Active UTP Transceiver Hub. Video/Data up to one mile. Automatic Picture and Gain control. 1U EIA 19" Rack Chassis, 115/230VAC Input, UL Listed (UL2044), cUL Listed.	2208.89
HubWayEX16SP	16 Port Active UTP Transceiver Hub w/Isolated Integral camera power. Individually selectable for 24VAC or 28VAC at 1 amp per port. Video/Data up to one mile. Automatic Picture and Gain control. 1U EIA 19" Rack Chassis, 115/230VAC Input, UL Listed (UL2044), cUL Listed.	2670.56
Active UTP Transceiver Module		
MODEL	DESCRIPTION	PRICE
HubWayEX1	Single Port Active UTP Transceiver Module. Video/Data up to one mile. Automatic Picture and Gain control. High Impact Insulated Housing. 6VAC-24VAC or 12VDC-24VDC input, UL Listed (UL2044), cUL Listed.	166.67
UTP Power Injector		
MODEL	DESCRIPTION	PRICE
HubWayEXP	UTP Power Injector, 16 Isolated Power Ports. Individually selectable for 24VAC or 28VAC at 1 amp per port with pass-through video and data. 1U EIA 19" Rack Chassis, 115/230VAC Input, UL Listed (UL2044), cUL Listed.	777.78
8-Channel Active UTP Transceiver Hubs with Integral Power (115VAC)		
<i>Units with CAT-5 & BNC connectors on rear of unit</i>		
MODEL	DESCRIPTION	PRICE
HubWayLD8CDS	8 Channel Active UTP Transceiver Hub with Integral Camera Power, Video/Data up to 3000 ft., 5 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115VAC Input, UL Listed (UL2044), cUL Listed.	1159.44
HubWayLD82CDS	8 Channel Active UTP Transceiver Hub with Integral Camera Power, Video/Data up to 3000 ft., 5 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115VAC Input, UL Listed (UL2044), cUL Listed, includes 8 UL Listed Accessory HubWayAv Video Balun/Combiners for 24VAC cameras.	1355.00
HubWayLD83CDS	8 Channel Active UTP Transceiver Hub with Integral Camera Power, Video/Data up to 3000 ft., 5 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115VAC Input, UL Listed (UL2044), cUL Listed, includes 8 UL Listed Accessory HubWayDv Video Balun/Combiners for 12VDC cameras.	1446.11

8-Channel Active UTP Transceiver Hubs with Integral Power (115VAC)		
<i>Units with CAT-5 connectors on front & BNC connectors on rear of unit</i>		
MODEL	DESCRIPTION	PRICE
HubWayLD8CD	8 Channel Active UTP Transceiver Hub with Integral Camera Power, Video/Data up to 3000 ft., 5 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115VAC Input, UL Listed (UL2044), cUL Listed.	1159.44
HubWayLD82CD	8 Channel Active UTP Transceiver Hub with Integral Camera Power, Video/Data up to 3000 ft., 5 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115VAC Input, UL Listed (UL2044), cUL Listed, includes 8 UL Listed Accessory HubWayAv Video Balun/Combiners for 24VAC cameras.	1355.00
HubWayLD83CD	8 Channel Active UTP Transceiver Hub with Integral Camera Power, Video/Data up to 3000 ft., 5 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115VAC Input, UL Listed (UL2044), cUL Listed, includes 8 UL Listed Accessory HubWayDv Video Balun/Combiners for 12VDC cameras.	1446.11
8-Channel Active UTP Transceiver Hubs with Integral Power (115/230VAC)		
<i>Units with CAT-5 & BNC connectors on rear of unit</i>		
MODEL	DESCRIPTION	PRICE
HubWayLD8DS	8 Channel Active UTP Transceiver Hub with Integral Camera Power, Video/Data up to 3000 ft., 5 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115/230VAC Input, UL Listed (UL2044).	1159.44
HubWayLD82DS	8 Channel Active UTP Transceiver Hub with Integral Camera Power, Video/Data up to 3000 ft., 5 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115/230VAC Input, UL Listed (UL2044), includes 8 UL Listed Accessory HubWayAv Video Balun/Combiners for 24VAC cameras.	1355.00
HubWayLD83DS	8 Channel Active UTP Transceiver Hub with Integral Camera Power, Video/Data up to 3000 ft., 5 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115/230VAC Input, UL Listed (UL2044), includes 8 UL Listed Accessory HubWayDv Video Balun/Combiners for 12VDC cameras.	1446.11
<i>Units with CAT-5 connectors on front & BNC connectors on rear of unit</i>		
MODEL	DESCRIPTION	PRICE
HubWayLD8D	8 Channel Active UTP Transceiver Hub with Integral Camera Power, Video/Data up to 3000 ft., 5 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115/230VAC Input, UL Listed (UL2044).	1159.44
HubWayLD82D	8 Channel Active UTP Transceiver Hub with Integral Camera Power, Video/Data up to 3000 ft., 5 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115/230VAC Input, includes 8 UL Listed Accessory HubWayAv Video Balun/Combiners for 24VAC cameras.	1355.00
HubWayLD83D	8 Channel Active UTP Transceiver Hub with Integral Camera Power, Video/Data up to 3000 ft., 5 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115/230VAC Input, includes 8 UL Listed Accessory HubWayDv Video Balun/Combiners for 12VDC cameras.	1446.11

8-Channel Active UTP Transceiver Hubs with Integral Isolated Power (115/230VAC)		
<i>Units with CAT-5 connectors on front & BNC connectors on rear of unit</i>		
MODEL	DESCRIPTION	PRICE
HubWayLD8Di	8 Channel Active UTP Transceiver Hub with Integral Camera Power, Video/Data up to 3000 ft., 8 amp total current, individually selectable 24VAC or 28VAC isolated PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115/230VAC Input, UL Listed (UL2044), cUL Listed.	1292.78
HubWayLD82Di	8 Channel Active UTP Transceiver Hub with Integral Camera Power, Video/Data up to 3000 ft., 8 amp total current, individually selectable 24VAC or 28VAC isolated PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115/230VAC Input, UL Listed (UL2044), cUL Listed, includes 8 UL Listed Accessory HubWayAv Video Balun/Combiners for 24VAC cameras.	1488.33
HubWayLD83Di	8 Channel Active UTP Transceiver Hub with Integral Camera Power, Video/Data up to 3000 ft., 8 amp total current, individually selectable 24VAC or 28VAC isolated PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115/230VAC Input, UL Listed (UL2044), cUL Listed, includes 8 UL Listed Accessory HubWayDv Video Balun/Combiners for 12VDC cameras.	1579.44
16-Channel Active UTP Transceiver Hubs with Integral Power (115VAC)		
<i>Units with CAT-5 connectors on front & BNC connectors on rear of unit</i>		
MODEL	DESCRIPTION	PRICE
HubWayLD16CD	16 Channel Active UTP Transceiver Hub with Integral Camera Power, Video/Data up to 3000 ft., 10 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115VAC Input, UL Listed (UL2044), cUL Listed.	2048.33
HubWayLD162CD	16 Channel Active UTP Transceiver Hub with Integral Camera Power, Video/Data up to 3000 ft., 10 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115VAC Input, UL Listed (UL2044), cUL Listed, includes 16 UL Listed Accessory HubWayAv Video Balun/Combiners for 24VAC cameras.	2439.44
HubWayLD163CD	16 Channel Active UTP Transceiver Hub with Integral Camera Power, Video/Data up to 3000 ft., 10 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115VAC Input, UL Listed (UL2044), cUL Listed, includes 16 UL Listed Accessory HubWayDv Video Balun/Combiners for 12VDC cameras.	2621.67
16-Channel Active UTP Transceiver Hubs with Integral Power (115/230VAC)		
<i>Units with CAT-5 connectors on front & BNC connectors on rear of unit</i>		
MODEL	DESCRIPTION	PRICE
HubWayLD16D	16 Channel Active UTP Transceiver Hub with Integral Camera Power, Video/Data up to 3000 ft., 10 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115/230VAC Input, UL Listed (UL2044).	2048.33
HubWayLD162D	16 Channel Active UTP Transceiver Hub with Integral Camera Power, Video/Data up to 3000 ft., 10 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115/230VAC Input, UL Listed (UL2044), includes 16 UL Listed Accessory HubWayAv Video Balun/Combiners for 24VAC cameras.	2439.44
HubWayLD163D	16 Channel Active UTP Transceiver Hub with Integral Camera Power, Video/Data up to 3000 ft., 10 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115/230VAC Input, UL Listed (UL2044), includes 16 UL Listed Accessory HubWayDv Video Balun/Combiners for 12VDC cameras.	2621.67

16-Channel Active UTP Transceiver Hubs with Integral Isolated Power (115/230VAC)		
<i>Units with CAT-5 connectors on front & BNC connectors on rear of unit</i>		
MODEL	DESCRIPTION	PRICE
HubWayLD16Di	16 Channel Active UTP Transceiver Hub with Integral Camera Power, Video/Data up to 3000 ft., 16 amp total current, individually selectable 24VAC or 28VAC isolated PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115/230VAC Input, UL Listed (UL2044), cUL Listed.	2315.00
HubWayLD162Di	16 Channel Active UTP Transceiver Hub with Integral Camera Power, Video/Data up to 3000 ft., 16 amp total current, individually selectable 24VAC or 28VAC isolated PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115/230VAC Input, includes 16 UL Listed Accessory HubWayAv Video Balun/Combiners for 24VAC cameras.	2706.11
HubWayLD163Di	16 Channel Active UTP Transceiver Hub with Integral Camera Power, Video/Data up to 3000 ft., 16 amp total current, individually selectable 24VAC or 28VAC isolated PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115/230VAC Input, includes 16 UL Listed Accessory HubWayDv Video Balun/Combiners for 12VDC cameras.	2888.33
Active UTP Transceiver Hubs (115/230VAC)		
<i>Units with CAT-5 connectors on front & BNC connectors on rear of unit</i>		
MODEL	DESCRIPTION	PRICE
HubWayLDH8	8 Channel Active UTP Transceiver Hub, Video/Data up to 3000 ft., 1U EIA 19" Rack Mount Chassis, 115/230VAC Input, UL Listed (UL2044), cUL Listed.	964.44
HubWayLDH16	16 Channel Active UTP Transceiver Hub, Video/Data up to 3000 ft., 1U EIA 19" Rack Mount Chassis, 115/230VAC Input, UL Listed (UL2044), cUL Listed.	1853.33
Passive UTP Transceiver Hubs with Integral Power Wall Mount		
MODEL	DESCRIPTION	PRICE
HubSat4D	4 Channel Passive UTP Transceiver Hub with Integral Camera Power, Video/Data up to 750 ft., 4 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, encl. 8.5"H x 7.5"W x 3.5"D, 115VAC Input, UL Listed (UL2044), cUL Listed.	300.00
HubSat42D	4 Channel Passive UTP Transceiver Hub with Integral Camera Power, Video/Data up to 750 ft., 4 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, encl. 8.5"H x 7.5"W x 3.5"D, 115VAC Input, UL Listed (UL2044), cUL Listed, includes 4 UL Listed Accessory HubWayAv Video Balun/Combiners for 24VAC cameras.	397.78
HubSat43D	4 Channel Passive UTP Transceiver Hub with Integral Camera Power, Video/Data up to 750 ft., 4 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, encl. 8.5"H x 7.5"W x 3.5"D, 115VAC Input, UL Listed (UL2044), cUL Listed, includes 4 UL Listed Accessory HubWayDv Video Balun/Combiners for 12VDC cameras.	443.33
HubSat8D	8 Channel Passive UTP Transceiver Hub with Integral Camera Power, Video/Data up to 750 ft., 8 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, encl. 13.5"H x 13"W x 3.25"D, 115VAC Input, UL Listed (UL2044), cUL Listed.	566.67
HubSat82D	8 Channel Passive UTP Transceiver Hub with Integral Camera Power, Video/Data up to 750 ft., 8 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, encl. 13.5"H x 13"W x 3.25"D, 115VAC Input, UL Listed (UL2044), cUL Listed, includes 8 UL Listed Accessory HubWayAv Video Balun/Combiners for 24VAC cameras.	762.22
HubSat83D	8 Channel Passive UTP Transceiver Hub with Integral Camera Power, Video/Data up to 750 ft., 8 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, encl. 13.5"H x 13"W x 3.25"D, 115VAC Input, UL Listed (UL2044), cUL Listed, includes 8 UL Listed Accessory HubWayDv Video Balun/Combiners for 12VDC cameras.	853.33

Passive UTP Transceiver Hubs with Integral Isolated Power Wall Mount		
MODEL	DESCRIPTION	PRICE
HubSat4Di	4 Channel Passive UTP Transceiver Hub with Integral Camera Power, Video/Data up to 750 ft., 4 amp total current, individually selectable 24VAC or 28VAC isolated PTC outputs, encl. 8.5"H x 7.5"W x 3.5"D, 115VAC Input.	307.78
HubSat42Di	4 Channel Passive UTP Transceiver Hub with Integral Camera Power, Video/Data up to 750 ft., 4 amp total current, individually selectable 24VAC or 28VAC isolated PTC outputs, encl. 8.5"H x 7.5"W x 3.5"D, 115VAC Input, includes 4 HubWayAv Video Balun/Combiners for 24VAC cameras.	405.56
HubSat43Di	4 Channel Passive UTP Transceiver Hub with Integral Camera Power, Video/Data up to 750 ft., 4 amp total current, individually selectable 24VAC or 28VAC isolated PTC outputs, encl. 8.5"H x 7.5"W x 3.5"D, 115VAC Input, UL Listed (UL2044), cUL Listed, includes 4 HubWayDv Video Balun/Combiners for 12VDC cameras.	451.11
HubSat8Di	8 Channel Passive UTP Transceiver Hub with Integral Camera Power, Video/Data up to 750 ft., 8 amp total current, individually selectable 24VAC or 28VAC isolated PTC outputs, encl. 13.5"H x 13"W x 3.25"D, 115VAC Input.	582.22
HubSat82Di	8 Channel Passive UTP Transceiver Hub with Integral Camera Power, Video/Data up to 750 ft., 8 amp total current, individually selectable 24VAC or 28VAC isolated PTC outputs, encl. 13.5"H x 13"W x 3.25"D, 115VAC Input, includes 8 HubWayAv Video Balun/Combiners for 24VAC cameras.	777.78
HubSat83Di	8 Channel Passive UTP Transceiver Hub with Integral Camera Power, Video/Data up to 750 ft., 8 amp total current, individually selectable 24VAC or 28VAC isolated PTC outputs, encl. 13.5"H x 13"W x 3.25"D, 115VAC Input, includes 8 HubWayDv Video Balun/Combiners for 12VDC cameras.	868.89
Passive UTP Transceiver Hubs with Integral Power Outdoor		
MODEL	DESCRIPTION	PRICE
HubSat4WP	4 Channel Passive UTP Transceiver Hub with Integral Camera Power, Video/Data up to 750 ft., 4 amp total current, individually selectable 24VAC or 28VAC PTC outputs, NEMA 4/IP65 outdoor encl. 12"H x 8"W x 6"D, 115VAC Input.	388.00
HubSat42WP	4 Channel Passive UTP Transceiver Hub with Integral Camera Power, Video/Data up to 750 ft., 4 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, NEMA 4/IP65 outdoor encl. 12"H x 8"W x 6"D, 115VAC Input, includes 4 HubWayAv Video Balun/Combiners for 24VAC cameras.	485.78
HubSat43WP	4 Channel Passive UTP Transceiver Hub with Integral Camera Power, Video/Data up to 750 ft., 4 amp total current, individually selectable 24VAC or 28VAC PTC outputs, NEMA 4/IP65 outdoor encl. 12"H x 8"W x 6"D, 115VAC Input, includes 4 HubWayDv Video Balun/Combiners for 12VDC cameras.	531.33
Passive UTP Transceiver Hubs with Integral Isolated Power Outdoor		
MODEL	DESCRIPTION	PRICE
HubSat4WPI	4 Channel Passive UTP Transceiver Hub with Integral Camera Power, Video/Data up to 750 ft., 4 amp total current, individually selectable 24VAC or 28VAC isolated PTC outputs, NEMA 4/IP65 outdoor encl. 12"H x 8"W x 6"D, 115VAC Input.	395.78
HubSat42WPI	4 Channel Passive UTP Transceiver Hub with Integral Camera Power, Video/Data up to 750 ft., 4 amp total current, individually selectable 24VAC or 28VAC isolated PTC outputs, NEMA 4/IP65 outdoor encl. 12"H x 8"W x 6"D, 115VAC Input, includes 4 HubWayAv Video Balun/Combiners for 24VAC cameras.	493.56
HubSat43WPI	4 Channel Passive UTP Transceiver Hub with Integral Camera Power, Video/Data up to 750 ft., 4 amp total current, individually selectable 24VAC or 28VAC isolated PTC outputs, NEMA 4/IP65 outdoor encl. 12"H x 8"W x 6"D, 115VAC Input, includes 4 HubWayDv Video Balun/Combiners for 12VDC cameras.	539.11

Video Balun/Combiners		
MODEL	DESCRIPTION	PRICE
HubWayAv	Video Balun/Combiner - Video/Data/Power over a single CAT-5 cable, UL Listed.	28.89
HubWayAvPK	HubWayAv eight (8) pack	197.78
HubWayDv	Video Balun/Combiner - Video/Data/Power over a single CAT-5 cable for 12VDC Fixed or PTZ cameras, UL Listed.	42.22
HubWayDvPK	HubWayDv eight (8) pack	286.67
HubWayDvi	Video Balun/Combiner - Video/Data/Power over a single CAT-5 cable for non-isolated 12VDC Fixed or PTZ cameras, UL Listed.	52.22
HubWayDviPK	HubWayDvi eight (8) pack	354.44
HubWayAv2	Slim-line Video Balun/Combiner - Video/Data/Power over a single CAT-5 cable	28.89
HubWayAv2PK	HubWayAv2 eight (8) pack	197.78
HubWayAvP	Slim-line Video Balun/Combiner - Video/Power over a single CAT-5 cable	28.89
HubWayAvPPK	HubWayAvP eight (8) pack	197.78
Video Surveillance UPS - Wall Mount		
MODEL	DESCRIPTION	PRICE
ReServ1	Video Surveillance UPS - twelve 24VAC true sine wave outputs rated @ 4 amp and four 12VDC regulated outputs rated @ 2 amp, encl. 13.5"H x 13"W x 3.25"D, Accommodates up to 2 - 12VDC/7AH batteries, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	371.11
ReServ2	Video Surveillance UPS - sixteen 24VAC true sine wave outputs rated @ 4 amp, encl. 13.5"H x 13"W x 3.25"D, Accommodates up to 2 - 12VDC/7AH batteries, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	371.11
ReServ3	Video Surveillance UPS - sixteen 12VDC regulated outputs rated @ 8 amp, encl. 13.5"H x 13"W x 3.25"D, Accommodates up to 2 - 12VDC/7AH batteries, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	371.11
Video Surveillance UPS - Outdoor		
MODEL	DESCRIPTION	PRICE
ReServ1WP	Outdoor Video Surveillance UPS - twelve 24VAC true sine wave outputs rated @ 4 amp and four 12VDC regulated outputs rated @ 2 amp, NEMA 4/IP66 outdoor encl. 17.5"H x 12"W x 6.625"D, Accommodates up to 2 - 12VDC/12AH batteries, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	522.22
ReServ2WP	Outdoor Video Surveillance UPS - sixteen 24VAC true sine wave outputs rated @ 4 amp, NEMA 4/IP66 outdoor encl. 17.5"H x 12"W x 6.625"D, Accommodates up to 2 - 12VDC/12AH batteries, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	522.22
ReServ3WP	Outdoor Video Surveillance UPS - sixteen 12VDC regulated outputs rated @ 8 amp, NEMA 4/IP66 outdoor encl. 17.5"H x 12"W x 6.625"D, Accommodates up to 2 - 12VDC/12AH batteries, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	522.22
CCTV Power Supplies AC (Fused)		
MODEL	DESCRIPTION	PRICE
ALTV244	4 Output CCTV Power Supply - 24VAC @ 4 amp or 28VAC @ 3.5 amp, fused outputs, encl. 8.5"H x 7.5"W x 3.5"D, 115VAC input.	87.33
ALTV244UL	4 Output CCTV Power Supply - 24VAC @ 3.5 amp or 28VAC @ 3 amp, fused outputs, encl. 8.5"H x 7.5"W x 3.5"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	98.22
ALTV244175	4 Output CCTV Power Supply - 24VAC @ 7.25 amp or 28VAC @ 6.25 amp, fused outputs, encl. 8.5"H x 7.5"W x 3.5"D, 115VAC input.	133.11
ALTV244175UL	4 Output CCTV Power Supply - 24VAC @ 7 amp or 28VAC @ 6.25 amp, fused outputs, encl. 12.25"H x 7.75"W x 4.5"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	148.67
ALTV244300	4 Output CCTV Power Supply - 24VAC @ 14 amp or 28VAC @ 12.5 amp, fused outputs, encl. 8.5"H x 7.5"W x 3.5"D, 115VAC input.	202.22
ALTV248	8 Output CCTV Power Supply - 24VAC @ 4 amp or 28VAC @ 3.5 amp, fused outputs, encl. 8.5"H x 7.5"W x 3.5"D, 115VAC input.	108.02
ALTV248UL	8 Output CCTV Power Supply - 24VAC @ 3.5 amp or 28VAC @ 3 amp, fused outputs, encl. 8.5"H x 7.5"W x 3.5"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	110.49
ALTV248175UL	8 Output CCTV Power Supply - 24VAC @ 7 amp or 28VAC @ 6.25 amp, fused outputs, encl. 12.25"H x 7.75"W x 4.5"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	158.89
ALTV248300	8 Output CCTV Power Supply - 24VAC @ 14 amp or 28VAC @ 12.5 amp, fused outputs, encl. 8.5"H x 7.5"W x 3.5"D, 115VAC input.	224.89
ALTV248300UL	8 Output CCTV Power Supply - 24VAC @ 12.5 amp or 28VAC @ 10 amp, fused outputs, encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	224.89

CCTV Power Supplies AC (Fused)		
MODEL	DESCRIPTION	PRICE
ALTV248300ULM	8 Output CCTV Power Supply - 24VAC @ 12.5 amp or 28VAC @ 10 amp, fused outputs, encl. 8.5"H x 7.5"W x 3.75"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	213.33
ALTV248600	8 Output CCTV Power Supply - 24VAC @ 28 amp or 28VAC @ 25 amp, fused outputs, encl. 13.5"H x 13"W x 3.25"D, 115VAC input.	310.89
ALTV248600UL	8 Output CCTV Power Supply - 24VAC @ 25 amp or 28VAC @ 20 amp, fused outputs, encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	310.89
ALTV2416	16 Output CCTV Power Supply - 24VAC @ 8 amp or 28VAC @ 7 amp, fused outputs, encl. 8.5"H x 7.5"W x 3.5"D, 115VAC input.	183.93
ALTV2416ULX	16 Output CCTV Power Supply - 24VAC @ 7 amp or 28VAC @ 6.25 amp, fused outputs, encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	186.42
ALTV2416350	16 Output CCTV Power Supply - 24VAC @ 14 amp or 28VAC @ 12.5 amp, fused outputs, encl. 13.5"H x 13"W x 3.25"D, 115VAC input.	243.33
ALTV2416300UL	16 Output CCTV Power Supply - 24VAC @ 12.5 amp or 28VAC @ 10 amp, fused outputs, encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	243.33
ALTV2416300ULM	16 Output CCTV Power Supply - 24VAC @ 12.5 amp or 28VAC @ 10 amp, fused outputs, encl. 8.5"H x 7.5"W x 3.75"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	232.22
ALTV2416600	16 Output CCTV Power Supply - 24VAC @ 28 amp or 28VAC @ 25 amp, fused outputs, encl. 13.5"H x 13"W x 3.25"D, 115VAC input.	334.67
ALTV2416600UL	16 Output CCTV Power Supply - 24VAC @ 25 amp or 28VAC @ 20 amp, fused outputs, encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	334.67
ALTV2432350	32 Output CCTV Power Supply - 24VAC @ 14 amp or 28VAC @ 12.5 amp, fused outputs, encl. 13.5"H x 13"W x 3.25"D, 115VAC input.	300.00
ALTV2432300UL	32 Output CCTV Power Supply - 24VAC @ 12.5 amp or 28VAC @ 10 amp, fused outputs, encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	300.00
ALTV2432600	32 Output CCTV Power Supply - 24VAC @ 28 amp or 28VAC @ 25 amp, fused outputs, encl. 13.5"H x 13"W x 3.25"D, 115VAC input.	345.56
ALTV2432600UL	32 Output CCTV Power Supply - 24VAC @ 25 amp or 28VAC @ 20 amp, fused outputs, encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	345.56
CCTV Power Supplies AC (PTCs)		
MODEL	DESCRIPTION	PRICE
ALTV244CB	4 Output CCTV Power Supply - 24VAC @ 4 amp or 28VAC @ 3.5 amp, PTC outputs, encl. 8.5"H x 7.5"W x 3.5"D, 115VAC input.	87.33
ALTV244ULCB	4 Output CCTV Power Supply - 24VAC @ 3.5 amp or 28VAC @ 3 amp, PTC Class 2 power limited outputs, encl. 8.5"H x 7.5"W x 3.5"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	98.22
ALTV244175CB	4 Output CCTV Power Supply - 24VAC @ 7.25 amp or 28VAC @ 6.25 amp, PTC outputs, encl. 8.5"H x 7.5"W x 3.5"D, 115VAC input.	133.11
ALTV244175ULCB	4 Output CCTV Power Supply - 24VAC @ 7 amp or 28VAC @ 6.25 amp, PTC Class 2 power limited outputs, encl. 12.25"H x 7.75"W x 4.5"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	148.67
ALTV244300CB	4 Output CCTV Power Supply - 24VAC @ 14 amp or 28VAC @ 12.5 amp, PTC outputs, encl. 8.5"H x 7.5"W x 3.5"D, 115VAC input.	202.22
ALTV248CB	8 Output CCTV Power Supply - 24VAC @ 4 amp or 28VAC @ 3.5 amp, PTC outputs, encl. 8.5"H x 7.5"W x 3.5"D, 115VAC input.	108.02
ALTV248ULCB	8 Output CCTV Power Supply - 24VAC @ 3.5 amp or 28VAC @ 3 amp, PTC Class 2 power limited outputs, encl. 8.5"H x 7.5"W x 3.5"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	110.49
ALTV248175ULCB	8 Output CCTV Power Supply - 24VAC @ 7 amp or 28VAC @ 6.25 amp, PTC Class 2 power limited outputs, encl. 12.25"H x 7.75"W x 4.5"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	158.89
ALTV248300CB	8 Output CCTV Power Supply - 24VAC @ 14 amp or 28VAC @ 12.5 amp, PTC outputs, encl. 13.5"H x 13"W x 3.25"D, 115VAC input.	224.89
ALTV248300ULCB	8 Output CCTV Power Supply - 24VAC @ 12.5 amp or 28VAC @ 10 amp, PTC Class 2 power limited outputs, encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	224.89
ALTV248300ULCBM	8 Output CCTV Power Supply - 24VAC @ 12.5 amp or 28VAC @ 10 amp, PTC Class 2 power limited outputs, encl. 8.5"H x 7.5"W x 3.75"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	213.33
ALTV248600CB	8 Output CCTV Power Supply - 24VAC @ 28 amp or 28VAC @ 25 amp, PTC outputs, encl. 13.5"H x 13"W x 3.25"D, 115VAC input.	310.89
ALTV248600ULCB	8 Output CCTV Power Supply - 24VAC @ 25 amp or 28VAC @ 20 amp, PTC Class 2 power limited outputs, encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	310.89

CCTV Power Supplies AC (PTCs)		
MODEL	DESCRIPTION	PRICE
ALTV2416CB	16 Output CCTV Power Supply - 24VAC @ 8 amp or 28VAC @ 7 amp, PTC outputs, encl. 8.5"H x 7.5"W x 3.5"D, 115VAC input.	183.93
ALTV2416ULCBX	16 Output CCTV Power Supply - 24VAC @ 7 amp or 28VAC @ 6 amp, PTC Class 2 power limited outputs, encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	186.42
ALTV2416350CB	16 Output CCTV Power Supply - 24VAC @ 14 amp or 28VAC @ 12.5 amp, PTC outputs, encl. 13.5"H x 13"W x 3.25"D, 115VAC input.	243.33
ALTV2416300ULCB	16 Output CCTV Power Supply - 24VAC @ 12.5 amp or 28VAC @ 10 amp, PTC Class 2 power limited outputs, encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	243.33
ALTV2416300UCBM	16 Output CCTV Power Supply - 24VAC @ 12.5 amp or 28VAC @ 10 amp, PTC Class 2 power limited outputs, encl. 8.5"H x 7.5"W x 3.75"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	232.22
ALTV2416600CB	16 Output CCTV Power Supply - 24VAC @ 28 amp or 28VAC @ 25 amp, PTC outputs, encl. 13.5"H x 13"W x 3.25"D, 115VAC input.	334.67
ALTV2416600ULCB	16 Output CCTV Power Supply - 24VAC @ 25 amp or 28VAC @ 20 amp, PTC Class 2 power limited outputs, encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	334.67
ALTV2432350CB	32 Output CCTV Power Supply - 24VAC @ 14 amp or 28VAC @ 12.5 amp, PTC outputs, encl. 13.5"H x 13"W x 3.25"D, 115VAC input.	300.00
ALTV2432300ULCB	32 Output CCTV Power Supply - 24VAC @ 12.5 amp or 28VAC @ 10 amp, PTC Class 2 power limited outputs, encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	300.00
ALTV2432600CB	32 Output CCTV Power Supply - 24VAC @ 28 amp or 28VAC @ 25 amp, PTC outputs, encl. 13.5"H x 13"W x 3.25"D, 115VAC input.	345.56
ALTV2432600ULCB	32 Output CCTV Power Supply - 24VAC @ 25 amp or 28VAC @ 20 amp, PTC Class 2 power limited outputs, encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	345.56
CCTV Power Supplies DC (Fused)		
MODEL	DESCRIPTION	PRICE
ALTV1224DC	8 Output CCTV Power Supply - 12VDC or 24VDC @ 4 amp, fused outputs, encl. 15.5"H x 12"W x 4.5"D, 115VAC input.	211.11
ALTV1224DC1	16 Output CCTV Power Supply - 12VDC or 24VDC @ 4 amp, fused outputs, encl. 15.5"H x 12"W x 4.5"D, 115VAC input.	231.11
ALTV1224DC2	16 Output CCTV Power Supply - 12VDC or 24VDC @ 6 amp, fused outputs, encl. 15.5"H x 12"W x 4.5"D, 115VAC input.	244.44
ALTV615DC1016	16 Output CCTV Power Supply - 6-15VDC @ 10 amp, fused outputs, encl. 13.5"H x 13"W x 3.25"D, 115VAC input.	277.78
CCTV Power Supplies DC (PTC)		
MODEL	DESCRIPTION	PRICE
ALTV615DC1016CB	16 Output CCTV Power Supply - 6-15VDC @ 10 amp, PTC outputs, encl. 13.5"H x 13"W x 3.25"D, 115VAC input.	277.78
CCTV Power Supplies AC & DC (Fused)		
MODEL	DESCRIPTION	PRICE
ALTV1224C4	4 Output CCTV Power Supply - two 24VAC @ 4 amp plus two 12VDC @ 4 amp, fused outputs, encl. 13.5"H x 13"W x 3.25"D, 115VAC input.	228.89
ALTV1224C	16 Output CCTV Power Supply - eight 24VAC @ 3.5 amp plus eight 12VDC @ 3.5 amp, fused outputs, encl. 15.5"H x 12"W x 4.5"D, 115VAC input.	260.00
CCTV Power Supplies AC Isolated (Fused)		
MODEL	DESCRIPTION	PRICE
ALTV248ULHI	8 Output Isolated CCTV Power Supply - 24VAC @ 12.5 amp, isolated fused Class 2 power limited outputs rated @ 1.56 amp each, encl. 12.25"H x 7.75"W x 4.5"D, 115VAC input, UL Listed (UL2044), cUL Listed.	236.67
ALTV248ULMI	8 Output Isolated CCTV Power Supply - 24VAC @ 12.5 amp, isolated fused Class 2 power limited outputs rated @ 1.56 amp each, encl. 8.5"H x 7.5"W x 3.75"D, 115VAC input, UL Listed (UL2044), cUL Listed.	227.78
ALTV2416ULI	16 Output Isolated CCTV Power Supply - 24VAC @ 25 amp, isolated fused Class 2 power limited outputs rated @ 1.56 amp each, encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL2044), cUL Listed.	344.44

CCTV Power Supplies AC Isolated (PTCs)		
MODEL	DESCRIPTION	PRICE
ALTV248ULCBHI	8 Output Isolated CCTV Power Supply - 24VAC @ 12.5 amp, isolated PTC Class 2 power limited outputs rated @ 1.56 amp each, encl. 12.25"H x 7.75"W x 4.5"D, 115VAC input, UL Listed (UL2044), cUL Listed.	236.67
ALTV248ULCBMI	8 Output Isolated CCTV Power Supply - 24VAC @ 12.5 amp, isolated PTC Class 2 power limited outputs rated @ 1.56 amp each, encl. 8.5"H x 7.5"W x 3.75"D, 115VAC input, UL Listed (UL2044), cUL Listed.	227.78
ALTV2416ULCBI	16 Output Isolated CCTV Power Supply - 24VAC @ 25 amp, isolated PTC Class 2 power limited outputs rated @ 1.56 amp each, encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL2044), cUL Listed.	344.44
CCTV Power Supplies DC (Fused)		
MODEL	DESCRIPTION	PRICE
ALTV615DC4UL	4 Output CCTV Power Supply - 6-12VDC @ 2.5 amp or 12-15VDC @ 2 amp, fused Class 2 power limited outputs, encl. 8.5"H x 7.5"W x 3.5"D, 24VAC 40VA or 24VAC 50VA input (Altronix Model# TP2440 or TP2450), UL Listed (UL2044), cUL Listed & CE Approved.	107.78
ALTV615DC44ULM	4 Output CCTV Power Supply - 6-15VDC @ 4 amp, fused Class 2 power limited outputs, encl. 8.5"H x 7.5"W x 3.75"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	141.11
ALTV615DC8UL	8 Output CCTV Power Supply - 6-15VDC @ 4 amp, fused Class 2 power limited outputs, encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	200.00
ALTV615DC48ULM	8 Output CCTV Power Supply - 6-15VDC @ 4 amp, fused Class 2 power limited outputs, encl. 8.5"H x 7.5"W x 3.75"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	163.33
CCTV Power Supplies DC (Fused)		
MODEL	DESCRIPTION	PRICE
ALTV615DC416UL	16 Output CCTV Power Supply - 6-15VDC @ 4 amp, fuse protected Class 2 Rated power limited outputs, encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	222.22
ALTV615DC616UL	16 Output CCTV Power Supply - 6-15VDC @ 6 amp, fuse protected non power limited outputs, encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	244.44
CCTV Power Supplies DC (PTCs)		
MODEL	DESCRIPTION	PRICE
ALTV615DC44UCBM	4 Output CCTV Power Supply - 6-15VDC @ 4 amp, PTC Class 2 power limited outputs, encl. 8.5"H x 7.5"W x 3.75"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	141.11
ALTV615DC8ULCB	8 Output CCTV Power Supply - 6-15VDC @ 4 amp, PTC Class 2 power limited outputs, encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	200.00
ALTV615DC48UCBM	8 Output CCTV Power Supply - 6-15VDC @ 4 amp, PTC Class 2 power limited outputs, encl. 8.5"H x 7.5"W x 3.75"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	163.33
ALTV615DC416UCB	16 Output CCTV Power Supply - 6-15VDC @ 4 amp, PTC Class 2 power limited outputs, encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	222.22
ALTV615DC416UBM	16 Output CCTV Power Supply - 6-15VDC @ 4 amp, PTC Class 2 power limited outputs, encl. 8.5"H x 7.5"W x 3.75"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	190.00
ALTV615DC616UCB	16 Output CCTV Power Supply - 6-15VDC @ 6 amp, PTC Class 2 power limited outputs, encl. 13.5"H x 13"W x 3.25"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	244.44
CCTV Power Supplies DC (PTC, 115/230VAC)		
MODEL	DESCRIPTION	PRICE
SAV4D	4 Output CCTV Power Supply - 12VDC @ 5 amp, PTC outputs, field installable grounded line cord, encl. 8.5"H x 7.5"W x 3.75"D, 115/230VAC input. UL Listed (UL2044), cUL Listed.	91.33
SAV9D	9 Output CCTV Power Supply - 12VDC @ 5 amp, PTC outputs, field installable grounded line cord, encl. 8.5"H x 7.5"W x 3.75"D, 115/230VAC input. UL Listed (UL2044), cUL Listed.	130.56
SAV18D	18 Output CCTV Power Supply - 12VDC @ 5 amp, PTC outputs, field installable grounded line cord, encl. 8.5"H x 7.5"W x 3.75"D, 115/230VAC input. UL Listed (UL2044), cUL Listed.	211.11
SAV182D	18 Output CCTV Power Supply - 12VDC @ 11 amp, PTC outputs, field installable grounded line cord, encl. 13.5"H x 13"W x 3.25"D, 115/230VAC input. UL Listed (UL2044), cUL Listed.	266.67
SAV36D	36 Output CCTV Power Supply - 12VDC @ 11 amp, PTC outputs, field installable grounded line cord, encl. 13.5"H x 13"W x 3.25"D, 115/230VAC input. UL Listed (UL2044), cUL Listed.	331.11

Rack Mount CCTV Power Supplies AC (Fused, 115VAC)		
MODEL	DESCRIPTION	PRICE
R248UL	8 Output Rack Mount CCTV Power Supply - 24VAC @ 3.5 amp or 28VAC @ 3 amp, fused outputs, 2U EIA 19" Rack Mount Chassis, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	283.89
R2416UL	16 Output Rack Mount CCTV Power Supply - 24VAC @ 7 amp or 28VAC @ 6 amp, fused outputs, 2U EIA 19" Rack Mount Chassis, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	377.22
R2416300UL	16 Output Rack Mount CCTV Power Supply - 24VAC @ 12.5 amp or 28VAC @ 10 amp, fused outputs, 2U EIA 19" Rack Mount Chassis, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	411.11
R2416600UL	16 Output Rack Mount CCTV Power Supply - 24VAC @ 25 amp or 28VAC @ 20 amp, fused outputs, 2U EIA 19" Rack Mount Chassis, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	488.89
R2432300UL	32 Output Rack Mount CCTV Power Supply - 24VAC @ 12.5 amp or 28VAC @ 10 amp, fused outputs, 2U EIA 19" Rack Mount Chassis, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	522.22
R2432600UL	32 Output Rack Mount CCTV Power Supply - 24VAC @ 25 amp or 28VAC @ 20 amp, fused outputs, 2U EIA 19" Rack Mount Chassis, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	600.00
VertiLine8C	8 Output Rack Mount CCTV Power Supply - 5 amp total current, individually selectable 24VAC or 28VAC fused outputs, 1U EIA 19" Rack Mount Chassis, 115VAC input, UL Listed (UL2044), cUL Listed.	381.11
VertiLine83C	8 Output Rack Mount CCTV Power Supply - 10 amp total current, individually selectable 24VAC or 28VAC fused outputs, 1U EIA 19" Rack Mount Chassis, 115VAC input, UL Listed (UL2044), cUL Listed.	417.56
VertiLine16C	16 Output Rack Mount CCTV Power Supply - 10 amp total current, individually selectable 24VAC or 28VAC fused outputs, 1U EIA 19" Rack Mount Chassis, 115VAC input, UL Listed (UL2044), cUL Listed.	488.33
VertiLine166C	16 Output Rack Mount CCTV Power Supply - 14 amp total current, individually selectable 24VAC or 28VAC fused outputs, 1U EIA 19" Rack Mount Chassis, 115VAC input, UL Listed (UL2044), cUL Listed.	564.33
VertiLine24C	24 Output Rack Mount CCTV Power Supply - 10 amp total current, individually selectable 24VAC or 28VAC fused outputs, 1U EIA 19" Rack Mount Chassis, 115VAC input, UL Listed (UL2044), cUL Listed.	522.67
VertiLine246C	24 Output Rack Mount CCTV Power Supply - 14 amp total current, individually selectable 24VAC or 28VAC fused outputs, 1U EIA 19" Rack Mount Chassis, 115VAC input, UL Listed (UL2044), cUL Listed.	603.89
Rack Mount CCTV Power Supplies AC (Fused, 115/230VAC)		
MODEL	DESCRIPTION	PRICE
VertiLine8	8 Output Rack Mount CCTV Power Supply - 5 amp total current, individually selectable 24VAC or 28VAC fused outputs, 1U EIA 19" Rack Mount Chassis, 115/230VAC input, UL Listed (UL2044).	381.11
VertiLine83	8 Output Rack Mount CCTV Power Supply - 10 amp total current, individually selectable 24VAC or 28VAC fused outputs, 1U EIA 19" Rack Mount Chassis, 115/230VAC input, UL Listed (UL2044).	417.56
VertiLine16	16 Output Rack Mount CCTV Power Supply - 10 amp total current, individually selectable 24VAC or 28VAC fused outputs, 1U EIA 19" Rack Mount Chassis, 115/230VAC input, UL Listed (UL2044).	488.33
VertiLine166	16 Output Rack Mount CCTV Power Supply - 14 amp total current, individually selectable 24VAC or 28VAC fused outputs, 1U EIA 19" Rack Mount Chassis, 115/230VAC input, UL Listed (UL2044).	564.33
VertiLine24	24 Output Rack Mount CCTV Power Supply - 10 amp total current, individually selectable 24VAC or 28VAC fused outputs, 1U EIA 19" Rack Mount Chassis, 115/230VAC input, UL Listed (UL2044).	522.67
VertiLine246	24 Output Rack Mount CCTV Power Supply - 14 amp total current, individually selectable 24VAC or 28VAC fused outputs, 1U EIA 19" Rack Mount Chassis, 115/230VAC input, UL Listed (UL2044).	603.89

Rack Mount CCTV Power Supplies AC Isolated (Fused, 115VAC)		
MODEL	DESCRIPTION	PRICE
R248ULI	8 Output Isolated Rack Mount CCTV Power Supply - 24VAC @ 12.5 amp, isolated fused Class 2 power limited outputs rated @ 1.56 amp each, 2U EIA 19" Rack Mount Chassis, 115VAC input, UL Listed (UL2044), cUL Listed.	372.22
R2416ULI	16 Output Isolated Rack Mount CCTV Power Supply - 24VAC @ 25 amp, isolated fused Class 2 power limited outputs rated @ 1.56 amp each, 2U EIA 19" Rack Mount Chassis, 115VAC input, UL Listed (UL2044), cUL Listed.	512.22
Rack Mount CCTV Power Supplies AC Isolated (Fused, 115/230VAC)		
MODEL	DESCRIPTION	PRICE
VertiLine8i	8 Output Isolated Rack Mount CCTV Power Supply - 24VAC or 28VAC @ 8 amp, isolated fused Class 2 power limited outputs rated @ 1 amp each, 1U EIA 19" Rack Mount Chassis, 115/230VAC input, UL Listed (UL2044), cUL Listed.	449.78
VertiLine16i	16 Output Isolated Rack Mount CCTV Power Supply - 24VAC or 28VAC @ 16 amp, isolated fused Class 2 power limited outputs rated @ 1 amp each, 1U EIA 19" Rack Mount Chassis, 115/230VAC input, UL Listed (UL2044), cUL Listed.	623.78
Rack Mount CCTV Power Supplies AC (PTCs, 115VAC)		
MODEL	DESCRIPTION	PRICE
R248ULCB	8 Output Rack Mount CCTV Power Supply - 24VAC @ 3.5 amp or 28VAC @ 3 amp, PTC Class 2 power limited outputs, 2U EIA 19" Rack Mount Chassis, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	283.89
R2416ULCB	16 Output Rack Mount CCTV Power Supply - 24VAC @ 7 amp or 28VAC @ 6 amp, PTC Class 2 power limited outputs, 2U EIA 19" Rack Mount Chassis, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	377.22
R2416300ULCB	16 Output Rack Mount CCTV Power Supply - 24VAC @ 12.5 amp or 28VAC @ 10 amp, PTC Class 2 power limited outputs, 2U EIA 19" Rack Mount Chassis, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	411.11
R2416600ULCB	16 Output Rack Mount CCTV Power Supply - 24VAC @ 25 amp or 28VAC @ 20 amp, PTC Class 2 power limited outputs, 2U EIA 19" Rack Mount Chassis, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	488.89
R2432300ULCB	32 Output Rack Mount CCTV Power Supply - 24VAC @ 12.5 amp or 28VAC @ 10 amp, PTC Class 2 power limited outputs, 2U EIA 19" Rack Mount Chassis, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	522.22
R2432600ULCB	32 Output Rack Mount CCTV Power Supply - 24VAC @ 25 amp or 28VAC @ 20 amp, PTC Class 2 power limited outputs, 2U EIA 19" Rack Mount Chassis, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	600.00
VertiLine8CD	8 Output Rack Mount CCTV Power Supply - 5 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115VAC input, UL Listed (UL2044), cUL Listed.	381.11
VertiLine83CD	8 Output Rack Mount CCTV Power Supply - 10 mp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115VAC input, UL Listed (UL2044), cUL Listed.	417.56
VertiLine16CD	16 Output Rack Mount CCTV Power Supply - 10 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115VAC input, UL Listed (UL2044), cUL Listed.	488.33
VertiLine166CD	16 Output Rack Mount CCTV Power Supply - 14 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115VAC input, UL Listed (UL2044), cUL Listed.	564.33
VertiLine24CD	24 Output Rack Mount CCTV Power Supply - 10 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115VAC input, UL Listed (UL2044), cUL Listed.	522.67
VertiLine246CD	24 Output Rack Mount CCTV Power Supply - 14 amp total current, individually selectable 24VAC or 28VAC PTC Class 2 power limited outputs, 1U EIA 19" Rack Mount Chassis, 115VAC input, UL Listed (UL2044), cUL Listed.	603.89

Rack Mount CCTV Power Supplies AC (PTCs, 115/230VAC)		
MODEL	DESCRIPTION	PRICE
VertiLine8D	8 Output Rack Mount CCTV Power Supply - 5 amp total current, PTC Class 2 power limited outputs, 24VAC or 28VAC selectable by output, 1U EIA 19" Rack Mount Chassis, 115/230VAC input, UL Listed (UL2044).	381.11
VertiLine83D	8 Output Rack Mount CCTV Power Supply - 10 amp total current, PTC Class 2 power limited outputs, 24VAC or 28VAC selectable by output, 1U EIA 19" Rack Mount Chassis, 115/230VAC input, UL Listed (UL2044).	417.56
VertiLine16D	16 Output Rack Mount CCTV Power Supply - 10 amp total current, PTC Class 2 power limited outputs, 24VAC or 28VAC selectable by output, 1U EIA 19" Rack Mount Chassis, 115/230VAC input, UL Listed (UL2044).	488.33
VertiLine166D	16 Output Rack Mount CCTV Power Supply - 14 amp total current, PTC Class 2 power limited outputs, 24VAC or 28VAC selectable by output, 1U EIA 19" Rack Mount Chassis, 115/230VAC input, UL Listed (UL2044).	564.33
VertiLine24D	24 Output Rack Mount CCTV Power Supply - 10 amp total current, PTC Class 2 power limited outputs, 24VAC or 28VAC selectable by output, 1U EIA 19" Rack Mount Chassis, 115/230VAC input, UL Listed (UL2044).	522.67
VertiLine246D	24 Output Rack Mount CCTV Power Supply - 14 amp total current, PTC Class 2 power limited outputs, 24VAC or 28VAC selectable by output, 1U EIA 19" Rack Mount Chassis, 115/230VAC input, UL Listed (UL2044).	603.89
Rack Mount CCTV Power Supplies AC Isolated (PTCs, 115VAC)		
MODEL	DESCRIPTION	PRICE
R248ULCBI	8 Output Isolated Rack Mount CCTV Power Supply - 24VAC @ 12.5 amp, isolated PTC Class 2 power limited outputs rated @ 1.56 amp each, 2U EIA 19" Rack Mount Chassis, 115VAC input, UL Listed (UL2044), cUL Listed.	372.22
R2416ULCBI	16 Output Isolated Rack Mount CCTV Power Supply - 24VAC @ 25 amp, isolated PTC Class 2 power limited outputs rated @ 1.56 amp each, 2U EIA 19" Rack Mount Chassis, 115VAC input, UL Listed (UL2044), cUL Listed.	512.22
Rack Mount CCTV Power Supplies AC Isolated (PTCs, 115/230VAC)		
MODEL	DESCRIPTION	PRICE
VertiLine8Di	8 Output Isolated Rack Mount CCTV Power Supply - 24VAC or 28VAC @ 8 amp, isolated PTC Class 2 power limited outputs rated @ 1 amp each, 1U EIA 19" Rack Mount Chassis, 115/230VAC input, UL Listed (UL2044), cUL Listed.	449.78
VertiLine16Di	16 Output Isolated Rack Mount CCTV Power Supply - 24VAC or 28VAC @ 16 amp, isolated PTC Class 2 power limited outputs rated @ 1 amp each, 1U EIA 19" Rack Mount Chassis, 115/230VAC input, UL Listed (UL2044), cUL Listed.	623.78

Rack Mount CCTV Power Supplies DC (Fused)		
MODEL	DESCRIPTION	PRICE
R615DC8UL	8 Output Rack Mount CCTV Power Supply - 6-15VDC @ 4 amp, fused Class 2 power limited outputs, 2U EIA 19" Rack Mount Chassis, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	377.78
R615DC416UL	16 Output Rack Mount CCTV Power Supply - 6-15VDC @ 4 amp, fused Class 2 power limited outputs, 2U EIA 19" Rack Mount Chassis, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	388.89
R615DC616UL	16 Output Rack Mount CCTV Power Supply - 6-15VDC @ 6 amp, fused Class 2 power limited outputs, 2U EIA 19" Rack Mount Chassis, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	411.11
R615DC1016	16 Output Rack Mount CCTV Power Supply - 6-15VDC @ 10 amp, fused outputs, 2U EIA 19" Rack Mount Chassis, 115VAC input.	433.33
Rack Mount CCTV Power Supplies DC (PTCs)		
MODEL	DESCRIPTION	PRICE
R615DC8ULCB	8 Output Rack Mount CCTV Power Supply - 6-15VDC @ 4 amp, PTC Class 2 power limited outputs, 2U EIA 19" Rack Mount Chassis, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	377.78
R615DC416ULCB	16 Output Rack Mount CCTV Power Supply - 6-15VDC @ 4 amp, PTC Class 2 power limited outputs, 2U EIA 19" Rack Mount Chassis, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	388.89
R615DC616ULCB	16 Output Rack Mount CCTV Power Supply - 6-15VDC @ 6 amp, PTC Class 2 power limited outputs, 2U EIA 19" Rack Mount Chassis, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	411.11
R615DC1016CB	16 Output Rack Mount CCTV Power Supply - 6-15VDC @ 10 amp, PTC outputs, 2U EIA 19" Rack Mount Chassis, 115VAC input.	433.33
Outdoor CCTV Power Supplies AC - UL Listed (Fused & PTCs)		
MODEL	DESCRIPTION	PRICE
WPTV244175UL	4 Output Outdoor CCTV Power Supply - 24VAC @ 7 amp or 28VAC @ 6.25 amp, 3 - PTC Class 2 power limited outputs rated @ 2.5 amp & 1 - fused output rated @ 10 amp, NEMA 4/IP65 outdoor encl. 12"H x 8"W x 6"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	236.67
WPTV244300UL	4 Output Outdoor CCTV Power Supply - 24VAC @ 12.5 amp or 28VAC @ 10 amp, 3 - PTC Class 2 power limited outputs rated @ 2.5 amp & 1 - fused output rated @ 15 amp, NEMA 4/IP65 outdoor encl. 12"H x 8"W x 6"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	271.11
Outdoor CCTV Power Supplies AC - UL Listed (Fused)		
MODEL	DESCRIPTION	PRICE
WPTV248UL	8 Output Outdoor CCTV Power Supply - 24VAC @ 3.5 amp or 28VAC @ 3 amp, fused outputs, NEMA 4/IP65 outdoor encl. 12"H x 8"W x 6"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	228.89
WPTV248175UL	8 Output Outdoor CCTV Power Supply - 24VAC @ 7 amp or 28VAC @ 6.25 amp, fused outputs, NEMA 4/IP65 outdoor encl. 12"H x 8"W x 6"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	243.33
WPTV248300UL	8 Output Outdoor CCTV Power Supply - 24VAC @ 12.5 amp or 28VAC @ 10 amp, fused outputs, NEMA 4/IP65 outdoor encl. 12"H x 8"W x 6"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	293.33
Outdoor CCTV Power Supplies AC - UL Listed (PTCs)		
MODEL	DESCRIPTION	PRICE
WPTV248ULCB	8 Output Outdoor CCTV Power Supply - 24VAC @ 3.5 amp or 28VAC @ 3 amp, PTC outputs, NEMA 4/IP65 outdoor encl. 12"H x 8"W x 6"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	228.89
WPTV248175ULCB	8 Output Outdoor CCTV Power Supply - 24VAC @ 7 amp or 28VAC @ 6.25 amp, PTC outputs, NEMA 4/IP65 outdoor encl. 12"H x 8"W x 6"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	243.33
WPTV248300ULCB	8 Output Outdoor CCTV Power Supply - 24VAC @ 12.5 amp or 28VAC @ 10 amp, PTC outputs, NEMA 4/IP65 outdoor encl. 12"H x 8"W x 6"D, 115VAC input, UL Listed (UL2044), cUL Listed & CE Approved.	293.33
WayPoint Outdoor CCTV AC Power Supplies 115/230VAC Input		
MODEL	DESCRIPTION	PRICE
WayPoint10A	1 Output Outdoor CCTV Power Supply - 24VAC @ 4 amp or 28VAC @ 3.5 amp, NEMA 4/4X, IP66-11 outdoor encl. 13.31"H x 11.31"W x 5.59"D, 115/230VAC input.	231.11
WayPoin17A	1 Output Outdoor CCTV Power Supply - 24VAC @ 7.25 amp or 28VAC @ 6.25 amp, NEMA 4/4X, IP66-11 outdoor encl. 13.31"H x 11.31"W x 5.59"D, 115/230VAC input.	244.44
WayPoint30A	2 Output Outdoor CCTV Power Supply - 24VAC @ 12.5 amp or 28VAC @ 10 amp, NEMA 4/4X, IP66-11 outdoor encl. 13.31"H x 11.31"W x 5.59"D, 115/230VAC input.	377.78
WayPoint Outdoor CCTV AC Power Supplies 277VAC Input		
MODEL	DESCRIPTION	PRICE
WayPoint307A	2 Output Outdoor CCTV Power Supply - 24VAC @ 12.5 amp or 28VAC @ 10 amp, NEMA 4/4X, IP66-11 outdoor encl. 13.31"H x 11.31"W x 5.59"D, 277VAC input.	422.22

WayPoint Outdoor CCTV DC Power Supply/Chargers 115/230VAC Input		
MODEL	DESCRIPTION	PRICE
WayPoint3	1 Output Outdoor CCTV Power Supply - 12VDC or 24VDC @ 2.5 amp, NEMA 4/4X, IP66-11 outdoor encl. 13.31"H x 11.31"W x 5.59"D, 115/230VAC input.	277.22
WayPoint5	1 Output Outdoor CCTV Power Supply - 12VDC or 24VDC @ 4 amp, NEMA 4/4X, IP66-11 outdoor encl. 13.31"H x 11.31"W x 5.59"D, 115/230VAC input.	322.22
WayPoint Outdoor CCTV DC Power Supply/Chargers 115VAC Input		
MODEL	DESCRIPTION	PRICE
WayPoint7	1 Output Outdoor CCTV Power Supply - 12VDC or 24VDC @ 6 amp, NEMA 4/4X, IP66-11 outdoor encl. 13.31"H x 11.31"W x 5.59"D, 115VAC input.	410.56
AC Transformers		
MODEL	DESCRIPTION	PRICE
T1656	Transformer - 16VAC/56VA (3.5 amp), 115VAC input.	46.67
T16100	Transformer - 16.5VAC/100VA (6.25 amp), 115VAC input	61.11
T2428100	Transformer - 24VAC/100VA (4 amp) or 28VAC/100VA (3.5 amp), 115VAC input, UL/cUL Recognized.	47.78
T24130D	Transformer - 24VAC/100VA (4 amp), 115VAC/230VAC input.	47.78
T2428175	Transformer - 24VAC/175VA (7.25 amp) or 28VAC/175VA (6 amp), 115VAC input, UL/cUL Recognized.	65.33
T2428300	Transformer - 24VAC/300VA (12.5 amp) or 28VAC/300VA (10 amp), 115VAC input.	175.00
T2856	Transformer - 28VAC/56VA (2 amp), 115VAC input.	46.67
T2885D	Transformer - 28VAC/100VA (3.5 amp), 115VAC/230VAC input.	53.33
T28140D	Transformer - 28VAC/175VA (6.25 amp), 115VAC/230VAC input.	76.67
AC Transformers in Enclosures		
MODEL	DESCRIPTION	PRICE
T2428100C	Transformer - 24VAC/100VA (4 amp) or 28VAC/100VA (3.5 amp), encl. 5.625"H x 7"W x 4.5"D, 115VAC input.	110.00
T2428175C	Transformer - 24VAC/175VA (7.25 amp) or 28VAC/175VA (6 amp), encl. 5.625"H x 7"W x 4.5"D, 115VAC input.	127.78
T2428300E	Transformer - 24VAC/300VA (12.5 amp) or 28VAC/300VA (10 amp), encl. 8.5"H x 7.5"W x 3.5"D, 115VAC input.	240.00
T2856C	Transformer - 28VAC/56VA (2 amp), encl. 5.625"H x 7"W x 4.5"D, 115VAC input.	110.00
AC Plug-in Transformers		
MODEL	DESCRIPTION	PRICE
TP1220	Plug-in transformer - 12VAC/20VA, 115VAC input, UL Listed.	10.44
TP1620	Plug-in transformer - 16VAC/20VA, 115VAC input, UL Listed.	10.44
TP1640	Plug-in transformer - 16VAC/40VA, 115VAC input, UL Listed.	14.00
TP1650	Plug-in transformer - 16VAC/50VA, 115VAC input, UL Listed.	17.76
TP2420	Plug-in transformer - 24VAC/20VA, 115VAC input, UL Listed.	11.44
TP2440	Plug-in transformer - 24VAC/40VA, 115VAC input, UL Listed.	14.00
TP2450	Plug-in transformer - 24VAC/50VA, 115VAC input, UL Listed.	17.76

Relay Modules

MODEL	DESCRIPTION	PRICE
RAC24	Relay & Base - 24VAC operation, 45mA current draw, DPDT contacts rated @ 10 amp/220VAC or 28VDC, DIN Rail Mount, UL Recognized.	25.67
RAC120	Relay & Base - 120VAC operation, 12mA current draw, DPDT contacts rated @ 10 amp/220VAC or 28VDC, DIN Rail Mount, UL Recognized.	25.67
RB5	Relay Module - 6VDC or 12VDC operation, 120mA current draw, DPDT contacts rated @ 5 amp/220VAC or 28VDC.	14.44
RB524	Relay Module - 24VDC operation, 40mA current draw, DPDT contacts rated @ 5 amp/220VAC or 28VDC.	14.44
RB1224	Relay Module - 12VDC or 24VDC operation, 75mA current draw, DPDT contacts rated @ 5 amp/220VAC or 28VDC.	14.44
RBR1224	Electronic Ratchet/Toggle Relay Module - 12VDC to 24VDC operation, 3VDC to 24VDC Positive or negative sensitive trigger input, 20mA current draw, DPDT contacts rated @ 0.5 amp/120VAC or 2 amp/28VDC.	31.56
RB30	Heavy Duty Load Switching Relay Module - 12VDC or 24VDC operation, 95mA current draw, SPDT contact rated @ 30 amp/120VAC or 28VDC.	23.33
RB610	Break Away Relay 6 Pack - 12VDC or 24VDC operation, 50mA current draw, SPDT contact rated @ 10 amp/120VAC or 28VDC.	43.33
RBSN	Relay Module - 12VDC or 24VDC operation, 15mA current draw, DPDT contacts rated @ 1 amp/120VAC or 2 amp/28VDC.	14.44
RBSNTTL	Sensitive Relay Module - 12VDC to 24VDC operation, 3VDC to 24VDC isolated positive or negative trigger input, 18mA current draw, DPDT contacts rated @ 1 amp/120VAC or 2 amp/28VDC.	20.00
RBST	Relay Module - 6VDC, 12VDC or 24VDC operation, 30mA current draw, DPDT contacts rated @ 1 amp/120VAC or 2 amp/28VDC.	14.44
RBTUL	Sensitive Relay Module - 12VDC or 24VDC operation, 3VDC to 24VDC positive trigger input, 30mA current draw, SPDT contact rated @ 1 amp/28VDC, Includes Snap Track, UL Listed Burglary (UL749R).	25.67
RBUL	Relay Module - 12VDC or 24VDC operation, 30mA current draw, SPDT contact rated @ 1 amp/28VDC, Includes Snap Track, UL Listed Burglary (UL749R).	15.22
RB7	Ultra Sensitive Relay Cluster - 12VDC or 24VDC operation, 3VDC to 24VDC positive trigger inputs, Seven independent isolated SPDT contacts rated @ 1 amp/120VAC or 28VDC.	100.00
RBOC7	Open Collector Module - 12VDC or 24VDC operation, 3VDC to 24VDC positive trigger inputs, Seven independent open collector outputs capable of sinking 100mA each.	77.78
RDC12	DIN Rail Mount UL Recognized Relay & Base - 12VDC operation, 86mA current draw, DPDT contacts rated @ 10 amp/220VAC or 28VDC.	25.67
RDC24	DIN Rail Mount UL Recognized Relay & Base - 24VDC operation, 43mA current draw, DPDT contacts rated @ 10 amp/220VAC or 28VDC.	25.67
RDC48	DIN Rail Mount UL Recognized Relay & Base - 48VDC operation, 20mA current draw, DPDT contacts rated @ 10 amp/220VAC or 28VDC.	25.67

Programmable Timers		
MODEL	DESCRIPTION	PRICE
6030	Bell Cut-Off Timer - 6VDC or 12VDC, SPDT contacts rated @ 8 amp/115VAC.	19.78
6062	Multi-Function Timer - 12VDC or 24VDC operation, SPDT contacts rated @ 8 amp/115VAC, 1 sec. to 60 min. adjustable timing range. One second momentary relay activation at the end of timing cycle.	29.33
AT4	4 Channel 365 day/24 hr. Annual Event Timer - 12 to 24 volt AC or DC operation, Four SPDT contacts rated @ 10 amp/115VAC/28VDC, 254 daily/weekly events, 1778 weekly block events, 254 holiday exceptions, LCD display, built-in battery charger, encl. 12.25"H x 7.75"W x 4.5"D.	277.78
AT4B	4 Channel 365 day/24 hr. Annual Event Timer - 12 to 24 volt AC or DC operation, Four SPDT contacts rated @ 10 amp/115VAC/28VDC, 254 daily/weekly events, 1778 weekly block events, 254 holiday exceptions, LCD display, built-in battery charger.	255.56
DL1	Door Control Timer - 12 to 24 Volt AC or DC operation, SPDT contact rated @ 3 amp/120VAC/28VDC, Use with magnetic locks & electric strikes.	51.33
DL3	Door Control Timer w/sounder - 12 to 24 Volt AC or DC operation, SPDT contact rated @ 3 amp/120VAC/28VDC, Use with magnetic locks & electric strikes.	66.67
DPT724A	DIN Rail Mountable Annual Event Timer - 12 to 24 volt AC or DC operation, SPDT contact rated @ 10 amp/115VAC/28VDC, 365 day/24 hr. timer, LCD display, Programmable features: 50 individual daily/weekly events, 350 block events per week, 10 holiday dates.	138.89
DTMR1	DIN Rail Mountable Multi-Function Timer - 12VDC or 24VDC operation, SPDT contacts rated @ 8 amp/115VAC, 1 sec. to 60 min. adjustable timing range. One second momentary relay activation at the end of timing cycle, Includes Snap Track & mounting clips.	51.56
PT2724	2 Channel 365 day/24 hr. Annual Event Timer - 12 to 24 volt AC or DC operation, Two SPDT contacts rated @ 10 amp/115VAC/28VDC, 100 daily/weekly events, 700 weekly block events, 20 holiday exceptions, LCD display, built-in battery charger.	177.78
PT724A	1 Channel 365 day/24 hr. Annual Event Timer - 12 to 24 volt AC or DC operation, SPDT contact rated @ 10 amp/115VAC/28VDC, 50 daily/weekly events, 350 weekly block events, 10 holiday exceptions, LCD display, built-in battery charger.	118.89
PT724AE	1 Channel 365 day/24 hr. Annual Event Timer - 12 to 24 volt AC or DC operation, SPDT contact rated @ 10 amp/115VAC/28VDC, 50 daily/weekly events, 350 weekly block events, 10 holiday exceptions, LCD display, built-in battery charger, encl. 8.5"H x 7.5"W x 3.5"D.	160.00
TEMPO2	Universal Two Stage Timer - 12 or 24 volt AC or DC operation, SPDT contact rated @ 2 amp/115VAC/28VDC, adjustable timing range 1 sec.-60 seconds timed door release, daily weekly test mode, one shot activation, door prop alarm, EEPROM memory, LCD Display.	65.33

Power Distribution & Auxiliary Modules		
MODEL	DESCRIPTION	PRICE
ACM4	4 Output Access Power Controller Module - Converts one (1) 12 to 24 volt AC or DC input into four (4) fused power outputs, individually selectable Fail-Safe/Fail-Secure outputs or dry form "C" contacts, fire alarm disconnect is selectable by output, UL Listed sub-assembly.	100.00
ACM4E	4 Output Access Power Controller Module - Converts one (1) 12 to 24 volt AC or DC input into four (4) fused power outputs, individually selectable Fail-Safe/Fail-Secure outputs or dry form "C" contacts, fire alarm disconnect is selectable by output, encl. 8"H x 7.25"W x 3.5"D, UL Listed, cUL Listed.	142.22
ACM4CB	4 Output Access Power Controller Module - Converts one (1) 12 to 24 volt AC or DC input into four (4) PTC power outputs, individually selectable Fail-Safe/Fail-Secure outputs, fire alarm disconnect is selectable by output, UL Listed sub-assembly.	100.00
ACM4CBE	4 Output Access Power Controller Module - Converts one (1) 12 to 24 volt AC or DC input into four (4) PTC power outputs, individually selectable Fail-Safe/Fail-Secure outputs, fire alarm disconnect is selectable by output, encl. 8"H x 7.25"W x 3.5"D, UL Listed, cUL Listed.	142.22
ACM8	8 Output Access Power Controller Module - Converts one (1) 12 to 24 volt AC or DC input into eight (8) fused power outputs, individually selectable Fail-Safe/Fail-Secure outputs or dry form "C" contacts, fire alarm disconnect is selectable by output, UL Recognized Component.	133.33
ACM8E	8 Output Access Power Controller Module - Converts one (1) 12 to 24 volt AC or DC input into eight (8) fused power outputs, individually selectable Fail-Safe/Fail-Secure outputs or dry form "C" contacts, fire alarm disconnect is selectable by output, encl. 13.5"H x 13"W x 3.25"D, UL Listed, cUL Listed.	202.22
ACM8CB	8 Output Access Power Controller Module - Converts one (1) 12 to 24 volt AC or DC input into eight (8) PTC power outputs, individually selectable Fail-Safe/Fail-Secure outputs, fire alarm disconnect is selectable by output, UL Recognized Component.	133.33
ACM8CBE	8 Output Access Power Controller Module - Converts one (1) 12 to 24 volt AC or DC input into eight (8) PTC power outputs, individually selectable Fail-Safe/Fail-Secure outputs, fire alarm disconnect is selectable by output, encl. 13.5"H x 13"W x 3.25"D, UL Listed, cUL Listed.	202.22
MOM5	5 Output Access Power Distribution Module - Converts one (1) 12VDC or 24VDC input into five (5) power outputs, PTC Class 2 power limited outputs rated @ 2.5 amp, Fire Alarm interface, UL Recognized.	108.89
MOM5C	5 Output Access Power Distribution Module - Converts one (1) 12VDC or 24VDC input into five (5) power outputs, PTC Class 2 power limited outputs rated @ 2.5 amp, Fire Alarm interface, encl. 8"H x 7.25"W x 3.5"D. UL Listed (UL294/UL1481), CSFM & MEA Approved.	153.33
DP4	DIN Rail Mountable 4 Output Power Distribution Module - Converts AC or DC power input (28 volts @ 14 amp max.) into four (4) fused power outputs. Includes Snap Track & mounting clips.	53.33
PD4	4 Output Power Distribution Module - Converts AC or DC power input (28 volts @ 14 amp max.) into four (4) fused power outputs.	31.11
PD4CB	4 Output Power Distribution Module - Converts AC or DC power input (28 volts @ 14 amp max.) into four (4) PTC power outputs.	31.11
PD8	8 Output Power Distribution Module - Converts AC or DC power input (28 volts @ 14 amp max.) into eight (8) fused power outputs.	40.00
PD8CB	8 Output Power Distribution Module - Converts AC or DC power input (28 volts @ 14 amp max.) into eight (8) PTC power outputs.	40.00
PD4UL	4 Output Power Distribution Module - Converts AC or DC power input (28 volts @ 14 amp max.) into four (4) fused power outputs, UL Recognized.	33.33
PD4ULCB	4 Output Power Distribution Module - Converts AC or DC power input (28 volts @ 14 amp max.) into four (4) PTC power outputs, UL Recognized.	33.33
PD8UL	8 Output Power Distribution Module - Converts AC or DC power input (28 volts @ 14 amp max.) into eight (8) fused power outputs, UL Recognized.	42.22
PD8ULCB	8 Output Power Distribution Module - Converts AC or DC power input (28 volts @ 14 amp max.) into eight (8) PTC power outputs, UL Recognized.	42.22
PD16W	16 Output Power Distribution Module - Converts AC or DC power input (28 volts @ 14 amp max.) into sixteen (16) fused power outputs, UL Recognized.	75.56
PD16WCB	16 Output Power Distribution Module - Converts AC or DC power input (28 volts @ 14 amp max.) into sixteen (16) PTC power outputs, UL Recognized.	75.56
LPD	Low Power Disconnect Module - 12VDC/24VDC input, Disconnects at 10.5 volts (12 volt setting), 20 volts (24 volt setting)	17.78

Power Conversion Modules		
MODEL	DESCRIPTION	PRICE
VR1	Power Conversion Module - Converts 24VAC or 24VDC input into 12VDC rated @ 1 amp, Modular connector/cable assembly. High impact insulated housing.	41.33
VR1T	Power Conversion Module - Converts 24VAC or 24VDC input into 12VDC rated @ 1 amp, spring terminals. High impact insulated housing.	38.33
VR1TM5	Power Conversion Module - Converts 24VAC or 24VDC input into 5VDC rated @ 1 amp, spring terminals. High impact insulated housing.	38.33
VR2T	Power Conversion Module - Converts 24VAC or 24VDC input into 12VDC rated @ 0.5 amp spring terminals. High impact insulated housing.	29.67
VR3T	Power Conversion Module - Converts 24VDC input into 12VDC rated @ 2 amp, screw terminals. High impact insulated housing.	56.67
VR4T	Power Conversion Module - Converts 24VDC input into 12VDC rated @ 3 amp output, screw terminals. High impact insulated housing.	65.22
VR5T	Power Conversion Module - Converts 24VAC or 24VDC input into 12VDC rated @ 3 amp, spring terminals. High impact insulated housing.	70.78
VR5BT	Power Conversion Module/Battery Charger - Converts 24VAC or 24VDC input into 12VDC rated @ 3 amp, spring terminals. High impact insulated housing.	74.11
VB1	Power Conversion Module - Converts 12-24VDC input into regulated 24VDC rated @ 0.75 amp, Modular connector/cable assembly. High impact insulated housing.	41.33
VB1T	Power Conversion Module - Converts 12-24VDC input into regulated 24VDC rated @ 0.75 amp output, screw terminals. High impact insulated housing.	38.33
Siren Drivers		
MODEL	DESCRIPTION	PRICE
ALSD1	2 Channel Siren Driver - 6VDC to 12VDC operation, Yelp & Steady, High output, Current draw 0.5 to 1.8 amp is based on speaker resistance & input voltage.	20.67
ALSD2	2 Channel Siren Driver - 6VDC to 12VDC operation, Yelp & Steady, Current draw 0.3 to 1.22 amp is based on speaker resistance & input voltage.	14.89
Snap Track		
MODEL	DESCRIPTION	PRICE
ST1	Snap Track for mounting: RB5, RBSN, RBST, RB30, RB524, RB1224, RBSNTTL.	2.67
ST2	Snap Track for mounting: RB7, RBOC7.	6.67
ST3	Snap Track for mounting for: SMP3, SMP5, AL624, 6062, PT724, PT724A.	8.89
Rechargeable Batteries		
MODEL	DESCRIPTION	PRICE
BT124	Lead Acid Battery - 12VDC/4AH, Dimensions 4"H x 3.5"W x 2.76"D.	28.33
BT126	Lead Acid Battery - 12VDC/7AH, Dimensions 3.66"H x 5.94"W x 2.56"D.	35.56
BT1212	Lead Acid Battery - 12VDC/12AH, Dimensions 3.5"H x 5.94"W x 3.75"D.	80.00
BT1240	Lead Acid Battery - 12VDC/40AH, Dimensions 6.73"H x 7.72"W x 6.5"D.	195.00
Note: Other Batteries with different capacities are available. Contact us for a quote		
Battery/General Purpose Enclosures & Related Hardware		
MODEL	DESCRIPTION	PRICE
BC100	Enclosure - 8.5"H x 7.5"W x 3.5"D, 19 gauge steel. Fits 2 - 12VDC/4AH batteries or 1 - 12VDC/7AH battery.	37.78
BC200	Enclosure - 12.25"H x 7.75"W x 4.5"D, 19 gauge steel. Fits up to 2 - 12VDC/7AH batteries.	46.67
BC300	Enclosure - 13.5"H x 13"W x 3.25"D, 19 gauge steel, includes cam lock. Fits up to 2 - 12VDC/7AH batteries.	64.44
BC300R	Red Enclosure - 13.5"H x 13"W x 3.25"D, 19 gauge steel, includes cam lock. Fits up to 2 - 12VDC/7AH batteries.	64.44
BC400	Enclosure - 15.5"H x 12"W x 4.5"D, 19 gauge steel, includes cam lock. Fits up to 2 - 12VDC/12AH batteries.	93.33
BCS4G	Battery shelf for BC400 encl.	33.33

Battery/General Purpose Enclosures & Related Hardware		
MODEL	DESCRIPTION	PRICE
BC400SG	Enclosure - 15.5"H x 12"W x 4.5"D, 19 gauge steel, includes battery shelf (BCS4G) & cam lock. Fits up to 4 - 12VDC/12AH batteries.	128.89
BC400R	Red Enclosure - 15.5"H x 12"W x 4.5"D, 19 gauge steel, includes cam lock. Fits up to 2 - 12VDC/12AH batteries.	93.33
BCS4R	Red battery shelf for BC400R encl.	33.33
BC400SR	Red Enclosure - 15.5"H x 12"W x 4.5"D, 19 gauge steel, includes battery shelf (BCS4R) & cam lock. Fits up to 4 - 12VDC/12AH batteries.	128.89
BC600	Red Enclosure - 18"H x 14.5"W x 4.5"D, 19 gauge steel, includes cam lock. Fits up to 2 - 12VDC/12AH batteries.	120.00
BC600G	Enclosure - 18"H x 14.5"W x 4.5"D, 19 gauge steel, includes cam lock. Fits up to 2 - 12VDC/12AH batteries.	120.00
BC800	Enclosure - 26"H x 19"W x 6.25"D, 16 gauge steel, includes cam lock. Mounting provided for up to 2 - power supply/chargers & up to 3 - optional accessory modules, fits up to 4 - 12VDC/12AH batteries	360.36
BC1240	Enclosure - 9.5"H x 9.5"W x 7.5"D, 19 gauge steel, includes cam lock. Accommodates 1 - 12VDC/40AH battery.	87.78
CAB4	Enclosure - 5.625"H x 7"W x 4.5"D, 19 gauge steel. Accommodates 1 - 12VDC/12AH battery.	55.56
RE2	2U Rack Mount Battery Enclosure, fits up to four (4) 12VDC/7AH batteries with Quick connect terminals.	251.58
WP1	Enclosure - NEMA 4/IP65 outdoor rated 12"H x 8"W x 6"D.	173.33
WP2	Enclosure - NEMA 4/IP66 outdoor rated 17.5"H x 12"W x 6.625"D.	95.00
WP3	Enclosure - NEMA 4-4X/IP66-11 outdoor rated 13.31"H x 11.31"W x 5.59"D.	215.56
Component Accessories		
MODEL	DESCRIPTION	PRICE
BF3	Blade Fuse 3 amp (violet). Package of 25.	16.67
BF10	Blade Fuse 10 amp (red). Package of 25.	19.44
BF15	Blade Fuse 15 amp (blue). Package of 25.	16.67
BL2	2 - 8" Battery leads (Red & Black).	1.11
BL3	2 - 18" Battery leads (Red & Black).	2.22
BL4	1 - 8" Battery Jumper (Yellow).	2.22
BNC24J	Coax Jumper 24" Male to Male.	6.22
CAM1	Cam lock w/mounting hardware.	6.67
CLIP1	2 - DIN Rail Mounting Clips.	7.78
CP1	Conversion plate for mounting two (2) PD4/PD8 or two (2) MOM5 boards in BC400/BC400R enclosure.	15.56
D10	1 - 10" length of DIN Rail.	6.67
DK1	1 - DIN Rail Mount Kit - 1 piece of Snap Track and two (2) DIN Rail Mounting Clips.	22.22
FUSE1	Glass fuse - 3.5 amp (3AG). Package of 100	55.56
FUSE2	Glass fuse - 5 amp (3AG). Package of 100	55.56
FUSE3	Glass fuse - 10 amp (3AG). Package of 100	55.56
FUSE4	Glass fuse - 1 amp (3AG). Package of 100	55.56
FUSE5	Glass fuse - 5 amp slow blow (3AG). Package of 100	66.67
GL1	1 - 8" Ground Lead (Green).	1.11
LB2032	1 - Lithium battery (3v) for AT4, PT2724, PT724A & PT724AE.	4.44
LC1	6 ft. 2-Wire Line Cord.	2.67
LC2	6 ft. Grounded 3-Wire Line Cord.	5.56
SPACER1	5/8" Nylon Spacer. Package of 25.	8.33
TAPE1	Double Stick Tape Pads. Package of 25.	12.22
WPL2	Lock for WP2 Enclosure	66.67

ALTRONIX CORP. can modify these products or custom design & manufacture to your specifications. Contact us for a quote.

PAYMENT: Options Include Prepayment, C.O.D., or Open Account Net/30. Late Payments are subject to a service charge at the rate of 1.5% per month (18% annual rate).

SHIPPING: All shipments are F.O.B. our Brooklyn plant.